



Aztec G2

IP65

IK16 (150J)

Bulkhead

Class I

Surface

Community and Public

Aztec G2 is a vandal resistant bulkhead designed for community and public environments.

Standard Colours

Matt Black

- Product Information

Aztec G2's uniform illumination ensures a consistent light distribution, enhancing visibility and reducing glare. Incorporating a removable gear tray ensures Aztec G2 is quick and easy to maintain, whilst enabling sustainable technology upgrades. Applications include car parks, perimeter of buildings and communal areas.

Impact Resistance Rating: IK16 (150J). More information, [CLICK HERE](#).

Ingress Protection Rating: IP65. More information, [CLICK HERE](#).

Housing: Die cast aluminium body.

Paint: Polyester powder coat. All colours available, [CLICK HERE](#).

Diffuser: Opal polycarbonate diffuser secured with tamperproof screws.

Driver: Electronic control gear on a removable tray with fused plug & socket connector block.

Mounting: Wall or ceiling.

Cable Entry: Provision for conduit entry in the back.

■ **Technical Information**

AztecG2	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
Opal				
ATC-G2-3000N-X-MB	3055	28.9	106	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.5	CRI>80	-	L70B10>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	D	539	-
	Dimensions			
	304mm x 304mm x 127mm			
ATC-G2-4000N-X-MB	4174	39.4	106	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.5	CRI>80	-	L70B10>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	D	539	-
	Dimensions			
	304mm x 304mm x 127mm			
ATC-G2-4500N-X-MB	4597	44.8	103	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.5	CRI>80	-	L70B10>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	D	539	-
	Dimensions			
	304mm x 304mm x 127mm			

■ Fitting Options

Photo Electronic Cell	-PC
Microwave Sensor - Basic	-M1
Switch Dimming	-DI
DALI-2 Dimming / Monitoring	-DA
Maintained Emergency 3 Hour	-E3
Central Battery Maintained 110V	-EV
Change Over Relay, 240V Relay Supplied	-ER
Maintained Emergency 3 Hour, Self Test	-ES
Maintained Emergency 3 Hour, DALI	-ED
Matt Black	-MB
Corridor Function	-CF

- -DA/-DI and -M1 options can't be combined.
- -CF will only work if combined with -M1 or an external presence detection sensor supplied by others.
- For -M2 Microwave Sensor - Advanced, please contact technical sales on +44 (0)20 8254 2022 or email technical@designplan.co.uk.

