

Product Information

Mission CMS, utilising our <u>Mission</u> luminaire, provides versatile mounting options including suspended or surface mounting. Other Mission CMS options include speakers, dummy bodies, infill panels, cameras, sensors, PA and CCTV.

Each application is unique and will be catered to your requirements. As a guide, the weight for 1 metre of Mission CMS is 18.5 kg (indication only).

Applications include covered platforms and

underpasses.

TRUNKING

Impact Resistance Rating: N/A
Ingress Protection Rating: N/A
Housing: Extruded aluminium body

Paint: Polyester powder coat. All colours available,

CLICK HERE.
Diffuser: N/A
Driver: N/A

Mounting: Ceiling or cornice mounting.

Cable Entry: N/A LUMINAIRE

Impact Resistance Rating: IK16 (150J). More

information, CLICK HERE

Ingress Protection Rating: IP65. More information,

CLICK HERE

Housing: Extruded aluminium body with die cast aluminium end caps.

Paint: Polyester powder coat. All colours available, CLICK HERE

Diffuser: Opal polycarbonate diffuser in frame secured with tamperproof screws.

Driver: Electronic control gear on removable tray for ease of repair/upgrade with fused plug & socket connector block.

Mounting: Ceiling or cornice mounting.

Cable Entry: Via Mission CMS

Fitting Options

Pure White	-PW
Matt Silver	-MS







