



## Linilux Angled

IP54

IK12 (62.5J)

Linear

Class I

Surface

Community and Public

Custodial

Secure Healthcare

Transport

Linilux Angled is a vandal resistant luminaire specifically designed for challenging environments, such as custodial and secure healthcare facilities, transport applications and community and public installations.

Standard Colours

Textured White

Textured Black

Matt Titanium

### Product Information

Linilux Angled design directs light precisely where it's needed, reducing wasted illumination and minimising glare. Incorporating a removable gear tray ensures Linilux Angled is quick and easy to maintain, whilst enabling sustainable technology upgrades.

Custodial applications include association areas, education facilities, ancillary areas, police stations and law courts. Transport applications include office and back of house. Secure Health applications include corridors and circulation spaces.

**Impact Resistance Rating:** IK12 (62.5J). More information, [CLICK HERE](#).

**Ingress Protection Rating:** IP54. More information, [CLICK HERE](#).

**Housing:** Zinc coated steel body

**Paint:** Polyester powder coat. All colours available, [CLICK HERE](#).

**Diffuser:** Clear polycarbonate diffuser secured with tamperproof screws.

**Driver:** Electronic control gear on removable tray with fused plug & socket connector block.

**Mounting:** Wall or cornice mounting.

**Cable Entry:** Provision for conduit entry in back and ends.

## ■ Technical Information

LiniluxAngled	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
1245mm x 86mm 86mm				
LLXA-G1-4-1700N-TB	1779	16.7	106	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	5.6	CRI>80	-	L <sub>80B10</sub> >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	685	-
	Dimensions			
LLXA-G1-4-2300N-TB	2352	21.3	110	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	5.6	CRI>80	-	L <sub>80B10</sub> >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	685	-
	Dimensions			
LLXA-G1-4-2800N-TB	2876	26	110	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	5.6	CRI>80	-	L <sub>80B10</sub> >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	685	-
	Dimensions			
LLXA-G1-4-3500N-TB	3508	30.9	113	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	5.6	CRI>80	-	L <sub>80B10</sub> >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	685	-
	Dimensions			
LLXA-G1-4-1700W-TB	1771	15.7	112	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	5.6	CRI>80	-	L <sub>80B10</sub> >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	618	-
	Dimensions			

LinluxAngled	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
<b>1245mm x 86mm 86mm</b>				
LLXA-G1-4-2300W-TB	2331	20.2	115	3000
	<b>Weight (kg)</b>	<b>CRI</b>	<b>High Temp (°C)</b>	<b>LED Lifetime</b>
	5.6	CRI>80	-	L <sub>80B10</sub> >72,000h
	<b>Driver lifetime (up to hours)</b>	<b>LED Energy Rating</b>	<b>Emergency Output (Lum/lm)</b>	<b>Nightlight Output (Lum/lm)</b>
	100,000	C	618	-
	<b>Dimensions</b>			
<hr/>				
LLXA-G1-4-2800W-TB	2850	24.8	115	3000
	<b>Weight (kg)</b>	<b>CRI</b>	<b>High Temp (°C)</b>	<b>LED Lifetime</b>
	5.6	CRI>80	-	L <sub>80B10</sub> >72,000h
	<b>Driver lifetime (up to hours)</b>	<b>LED Energy Rating</b>	<b>Emergency Output (Lum/lm)</b>	<b>Nightlight Output (Lum/lm)</b>
	100,000	C	618	-
	<b>Dimensions</b>			
<hr/>				
LLXA-G1-4-3400W-TB	3413	29.9	114	3000
	<b>Weight (kg)</b>	<b>CRI</b>	<b>High Temp (°C)</b>	<b>LED Lifetime</b>
	5.6	CRI>80	-	L <sub>80B10</sub> >72,000h
	<b>Driver lifetime (up to hours)</b>	<b>LED Energy Rating</b>	<b>Emergency Output (Lum/lm)</b>	<b>Nightlight Output (Lum/lm)</b>
	100,000	C	618	-
	<b>Dimensions</b>			
<hr/>				
<b>1562mm x 90mm x 90mm</b>				
LLXA-G1-5-2700N-TB	2798	20.1	139	4000
	<b>Weight (kg)</b>	<b>CRI</b>	<b>High Temp (°C)</b>	<b>LED Lifetime</b>
	7	CRI>80	-	L <sub>80B10</sub> >72,000h
	<b>Driver lifetime (up to hours)</b>	<b>LED Energy Rating</b>	<b>Emergency Output (Lum/lm)</b>	<b>Nightlight Output (Lum/lm)</b>
	100,000	C	732	-
	<b>Dimensions</b>			
<hr/>				
LLXA-G1-5-3600N-TB	3688	25.9	142	4000
	<b>Weight (kg)</b>	<b>CRI</b>	<b>High Temp (°C)</b>	<b>LED Lifetime</b>
	7	CRI>80	-	L <sub>80B10</sub> >72,000h
	<b>Driver lifetime (up to hours)</b>	<b>LED Energy Rating</b>	<b>Emergency Output (Lum/lm)</b>	<b>Nightlight Output (Lum/lm)</b>
	100,000	C	732	-
	<b>Dimensions</b>			

LinluxAngled	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
<b>1562mm x 90mm x 90mm</b>				
LLXA-G1-5-4500N-TB	4548	31.5	144	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	7	CRI>80	-	L <sub>80B10</sub> >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	732	-
	Dimensions			
LLXA-G1-5-5300N-TB	5365	38	141	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	7	CRI>80	-	L <sub>80B10</sub> >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	732	-
	Dimensions			
LLXA-G1-5-2600W-TB	2655	18.7	142	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	7	CRI>80	-	L <sub>80B10</sub> >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	645	-
	Dimensions			
LLXA-G1-5-3500W-TB	3502	24.4	143	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	7	CRI>80	-	L <sub>80B10</sub> >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	645	-
	Dimensions			
LLXA-G1-5-4300W-TB	4362	30.2	145	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	7	CRI>80	-	L <sub>80B10</sub> >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	645	-
	Dimensions			

LinluxAngled	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
1562mm x 90mm x 90mm				
LLXA-G1-5-5100W-TB	5177	36.7	141	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	7	CRI>80	-	L80B10>72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	645	-
	Dimensions			

## Fitting Options

Coastal Paint Finish (Zone 2)	-Z2
DALI-2 Dimming / Monitoring	-DA
Maintained Emergency 3 Hour	-E3
Central Battery Maintained 110V	-EV
Change Over Relay, 240V Relay Supplied	-ER
Maintained Emergency 3 Hour, Self Test	-ES
Textured White	-TW
Textured Black	-TB
Matt Titanium	-MT

- For paint colour options, please replace -TB with required paint code.

