



## Quadrant S12

IP54

IK08 (5J)

Bulkhead

Class I

Recessed

Surface

Transport

Quadrant S12 is a bulkhead luminaire specifically designed in accordance with fire precautions for subsurface rail stations (Section 12).

Standard Colours

Textured White

Textured Black

Matt Titanium

### Product Information

Quadrant S12's opal diffuser provides a soft lit appearance, while providing uniform illumination, ensuring a consistent light distribution. Incorporating a removable gear tray ensures Quadrant S12 is quick and easy to maintain, whilst enabling sustainable technology upgrades.

Quadrant S12 complies with London Underground subsurface standard S1085 utilising low smoke, zero halogen cables and control gear.

Applications include ticket halls, general circulation and back of house.

**Impact Resistance Rating:** IK08 (5J). More information, [CLICK HERE](#).

**Ingress Protection Rating:** IP54. More information, [CLICK HERE](#).

**Housing:** Zinc coated steel body.

**Paint:** Polyester powder coat. All colours available, [CLICK HERE](#).

**Diffuser:** Lead crystal opal glass diffuser secured with tamperproof screws.

**Driver:** Electronic control gear on removal tray with fused plug & socket connector block. DALI driver as standard.

**Mounting:** Wall or ceiling.

**Cable Entry:** Provision for conduit entry in back and two sides.

## ■ Technical Information

QuadrantS12	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
Opal Glass				
DQ-800N-X-TB-ST-DA	714	7.6	94	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	3.6	CRI>80	-	L70B10>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	D	312	-
	Dimensions			
	254mm x 254mm x 95mm			
DQ-1100N-X-TB-ST-DA	1002	10.6	94	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	3.6	CRI>80	-	L70B10>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	D	312	-
	Dimensions			
	254mm x 254mm x 95mm			
DQ-1400N-X-TB-ST-DA	1428	15.7	91	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	3.6	CRI>80	-	L70B10>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	D	312	-
	Dimensions			
	254mm x 254mm x 95mm			
DQ-1900N-X-TB-ST-DA	1962	22.1	89	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	3.6	CRI>80	-	L70B10>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	D	312	-
	Dimensions			
	254mm x 254mm x 95mm			

## Fitting Options

Zone 2 (Seafront Areas)	-Z2
Photo Electronic Cell	-PC
Blank Ends	-BE
Semi-Recessed	-SR
Switch Dimming	-DI
DALI-2 Dimming / Monitoring	-DA
Maintained Emergency 3 Hour	-E3
Central Battery Maintained 110V	-EV
Change Over Relay, 240V Relay Supplied	-ER
Maintained Emergency 3 Hour, Self Test	-ES
Maintained Emergency 3 Hour, DALI	-ED
Textured White	-TW
Textured Black	-TB
Matt Titanium	-MT

- For paint colour options, please replace -TB with required paint code.
- -E3 option only available on non-DALI version.
- Please note the Quadrant now comes with Knock Outs for fixing and conduit holes and with no Besa Slots, the Gear Tray is also no longer secured with thumb screws. If you require a replacement gear tray and your fixings are thumb screws, please ask for QuadRetro trays.

