



## Quadratum G2 Surface

IP65

IK14 (100J)

Modular

Class I

Surface

Secure Healthcare

Transport

Quadratum G2 Surface is a vandal resistant luminaire specifically designed for challenging environments, such as secure healthcare facilities and transport applications.

Standard Colours

Textured White

### Product Information

Quadratum G2 Surface's opal diffuser provides a soft lit appearance, while providing uniform illumination, ensuring a consistent light distribution. Incorporating a removable gear tray ensures Quadratum G2 Surface is quick and easy to maintain, whilst enabling sustainable technology upgrades.

Custodial applications include video conferencing areas and education facilities. Secure Health applications include nurse stations, corridors and circulation spaces. Transport applications include ticket areas.

**Impact Resistance Rating:** IK14 (100J). More information, [CLICK HERE](#).

**Ingress Protection Rating:** IP65. More information, [CLICK HERE](#).

**Housing:** Mild steel body, zinc coated steel frame.

**Paint:** Polyester powder coat. All colours available, [CLICK HERE](#).

**Diffuser:** Opal polycarbonate diffuser in frame secured with tamperproof screws.

**Driver:** Electronic control gear on removal tray with fused plug & socket connector block.

**Mounting:** Ceiling.

**Cable Entry:** Provision for cable entry in back.

## ■ Technical Information

QuadratumG2Surface	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
<b>Opal</b>				
D936-G2-2000N-X-TW	2260	17.4	130	4000
	<b>Weight (kg)</b>	<b>CRI</b>	<b>High Temp (°C)</b>	<b>LED Lifetime</b>
	9.4	CRI>80	-	L <sub>80</sub> B <sub>10</sub> >72,000h
	<b>Driver lifetime (up to hours)</b>	<b>LED Energy Rating</b>	<b>Emergency Output (Lum/lm)</b>	<b>Nightlight Output (Lum/lm)</b>
	100,000	C	585	-
	<b>Dimensions</b>			
	598mm x 598mm x 82mm			
D936-G2-3000N-X-TW	3269	24.6	133	4000
	<b>Weight (kg)</b>	<b>CRI</b>	<b>High Temp (°C)</b>	<b>LED Lifetime</b>
	9.4	CRI>80	-	L <sub>80</sub> B <sub>10</sub> >72,000h
	<b>Driver lifetime (up to hours)</b>	<b>LED Energy Rating</b>	<b>Emergency Output (Lum/lm)</b>	<b>Nightlight Output (Lum/lm)</b>
	100,000	C	585	-
	<b>Dimensions</b>			
	598mm x 598mm x 82mm			
D936-G2-4000N-X-TW	4203	31.8	132	4000
	<b>Weight (kg)</b>	<b>CRI</b>	<b>High Temp (°C)</b>	<b>LED Lifetime</b>
	9.4	CRI>80	-	L <sub>80</sub> B <sub>10</sub> >72,000h
	<b>Driver lifetime (up to hours)</b>	<b>LED Energy Rating</b>	<b>Emergency Output (Lum/lm)</b>	<b>Nightlight Output (Lum/lm)</b>
	100,000	C	585	-
	<b>Dimensions</b>			
	598mm x 598mm x 82mm			
D936-G2-5000N-X-TW	5081	39.2	130	4000
	<b>Weight (kg)</b>	<b>CRI</b>	<b>High Temp (°C)</b>	<b>LED Lifetime</b>
	9.4	CRI>80	-	L <sub>80</sub> B <sub>10</sub> >72,000h
	<b>Driver lifetime (up to hours)</b>	<b>LED Energy Rating</b>	<b>Emergency Output (Lum/lm)</b>	<b>Nightlight Output (Lum/lm)</b>
	100,000	C	585	-
	<b>Dimensions</b>			
	598mm x 598mm x 82mm			
D936-G2-2000W-X-TW	2172	17.4	125	3000
	<b>Weight (kg)</b>	<b>CRI</b>	<b>High Temp (°C)</b>	<b>LED Lifetime</b>
	9.4	CRI>80	-	L <sub>80</sub> B <sub>10</sub> >72,000h
	<b>Driver lifetime (up to hours)</b>	<b>LED Energy Rating</b>	<b>Emergency Output (Lum/lm)</b>	<b>Nightlight Output (Lum/lm)</b>
	100,000	C	562	-
	<b>Dimensions</b>			
	598mm x 598mm x 82mm			

QuadratumG2Surface	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
<b>Opal</b>				
D936-G2-3000W-X-TW	3142	24.6	128	3000
	<b>Weight (kg)</b>	<b>CRI</b>	<b>High Temp (°C)</b>	<b>LED Lifetime</b>
	9.4	CRI>80	-	L <sub>80</sub> B <sub>10</sub> >72,000h
	<b>Driver lifetime (up to hours)</b>	<b>LED Energy Rating</b>	<b>Emergency Output (Lum/lm)</b>	<b>Nightlight Output (Lum/lm)</b>
	100,000	C	562	-
	<b>Dimensions</b>			
	598mm x 598mm x 82mm			
D936-G2-4000W-X-TW	4040	31.8	127	3000
	<b>Weight (kg)</b>	<b>CRI</b>	<b>High Temp (°C)</b>	<b>LED Lifetime</b>
	9.4	CRI>80	-	L <sub>80</sub> B <sub>10</sub> >72,000h
	<b>Driver lifetime (up to hours)</b>	<b>LED Energy Rating</b>	<b>Emergency Output (Lum/lm)</b>	<b>Nightlight Output (Lum/lm)</b>
	100,000	C	562	-
	<b>Dimensions</b>			
	598mm x 598mm x 82mm			
D936-G2-5000W-X-TW	4883	39.2	125	3000
	<b>Weight (kg)</b>	<b>CRI</b>	<b>High Temp (°C)</b>	<b>LED Lifetime</b>
	9.4	CRI>80	-	L <sub>80</sub> B <sub>10</sub> >72,000h
	<b>Driver lifetime (up to hours)</b>	<b>LED Energy Rating</b>	<b>Emergency Output (Lum/lm)</b>	<b>Nightlight Output (Lum/lm)</b>
	100,000	C	562	-
	<b>Dimensions</b>			
	598mm x 598mm x 82mm			

## Fitting Options

Switch Dimming	-DI
DALI-2 Dimming / Monitoring	-DA
Maintained Emergency 3 Hour	-E3
Maintained Emergency 3 Hour, Self Test	-ES
Maintained Emergency 3 Hour, DALI	-ED
Textured White	-TW

