



Tuscan Trunking

CMS/Trunking/Dummy Bodies

Class I

Surface

Community and Public

Custodial

Secure Healthcare

Transport

Tuscan Trunking is a cable management system specifically designed for challenging environments, such as custodial facilities, transport applications and community and public installations.

Product Information

Tuscan Trunking is a three-compartment trunking system for power, telephones, TV, alarm, door opening, CCTV or other required services neatly behind the light fitting. Available in 45 degree angle with straight sections supplied up to 1800mm in length (maintaining a 300mm centre).

Community and Public applications include subways and underpasses. Custodial applications include association areas, police stations and law courts. Each application is unique and will be catered to your requirements.

TRUNKING:

Impact Resistance Rating: N/A

Ingress Protection Rating: N/A

Housing: Zinc coated steel body.

Paint: Polyester powder coat. For all colours available, [CLICK HERE](#).

Diffuser: N/A

Driver: N/A

Mounting: Cornice

Cable Entry: 3 compartment CMS

LUMINAIRE:

Impact Resistance Rating: N/A

Ingress Protection Rating: . More information, [CLICK HERE](#).

Housing: Zinc coated steel gear tray and diffuser frame.

Paint: Polyester powder coat. For all colours available, [CLICK HERE](#).

Diffuser: Opal polycarbonate diffuser in frame secured with tamperproof screws.

Driver: Electronic control gear on removable tray with fused plug & socket connector block.

Mounting: In Tuscan Trunking section

Cable Entry: Via Tuscan CMS.

■ Technical Information

TuscanTrunking	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
L1500mm				
TRGT-5-6250N	4735	49.5	96	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	-	CRI>80	-	LED Lifetime >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	588	-
	Dimensions			
	1500mm			

■ Fitting Options

Coastal Paint Finish (Zone 2)	-Z2
Screw Allen Head	-SA
Maintained Emergency 3 Hour	-E3
Maintained Emergency 3 Hour, Self Test	-ES
Maintained Emergency 3 Hour, DALI	-ED

