



## Flair



Flair is a vandal resistant luminaire designed specifically for challenging environments, such as custodial facilities, transport applications and community and public installations.

### Standard Colours



### Product Information

Flair's uniform illumination ensures a consistent light distribution, enhancing visibility and reducing glare. Incorporating a removable gear tray ensures Flair is quick and easy to maintain, whilst enabling sustainable technology upgrades.

Transport applications include ticket areas, station forecourts and general circulation areas. Custodial applications include video conferencing and ancillary areas. Community and public applications include subways.

This luminaire is designed for longevity and sustainability and adheres to our circular design principles. We conduct a circular economy assessment using [TM66](#) and measure embodied carbon (kgCO<sub>2</sub>e) in accordance with [TM65.2](#).

**Impact Resistance Rating:** IK16 (150J). [Learn More.](#)

**Ingress Protection Rating:** IP65. [Learn More.](#)

**Housing:** Extruded aluminium body with die cast end caps.

**Paint:** Polyester powder coat. [All Colour Options Available Here.](#)

**Diffuser:** Clear polycarbonate diffuser in frame secured with tamperproof screws. Internal reflective louvre with opal liner.

**Driver:** Electronic control gear on removable tray for ease of repair/upgrade with fused plug & socket connector block.

**Mounting:** Ceiling.

**Cable Entry:** Provision for conduit entry in back.

**Design Life:** 30+ years. [Learn More.](#)

## ■ Technical Information

Flair	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
<b>L615mm Clear</b>				
FLR-2-1500N-P-MS	1064	11.5	92	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.4	CRI>80	-	L <sub>80</sub> B <sub>100</sub> >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	B	-	-
	Dimensions			
	150mm x 88mm			
FLR-2-2000N-P-MS	1421	15	95	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.4	CRI>80	-	L <sub>80</sub> B <sub>100</sub> >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	B	-	-
	Dimensions			
	150mm x 88mm			
FLR-2-2500N-P-MS	1779	18.7	95	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.4	CRI>80	-	L <sub>80</sub> B <sub>100</sub> >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	B	-	-
	Dimensions			
	150mm x 88mm			
FLR-2-3000N-P-MS	2234	23.6	94	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.4	CRI>80	-	L <sub>80</sub> B <sub>100</sub> >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	B	-	-
	Dimensions			
	150mm x 88mm			
FLR-2-1500W-P-MS	1011	11.5	88	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.4	CRI>80	-	L <sub>80</sub> B <sub>100</sub> >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	-	-
	Dimensions			
	150mm x 88mm			

Flair	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
<b>L615mm Clear</b>				
FLR-2-2000W-P-MS	1350	15	90	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.4	CRI>80	-	L <sub>80</sub> B <sub>100</sub> >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	-	-
	Dimensions			
	150mm x 88mm			
FLR-2-2500W-P-MS	1690	18.7	90	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.4	CRI>80	-	L <sub>80</sub> B <sub>100</sub> >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	-	-
	Dimensions			
	150mm x 88mm			
FLR-2-3000W-P-MS	2122	23.6	90	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.4	CRI>80	-	L <sub>80</sub> B <sub>100</sub> >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	-	-
	Dimensions			
	150mm x 88mm			
<b>L615mm Opal</b>				
FLR-2-1500N-X-MS	1206	15.4	78	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.4	CRI>80	-	L <sub>70</sub> B <sub>100</sub> >110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	-	-
	Dimensions			
	150mm x 88mm			
FLR-2-2000N-X-MS	1460	18.8	78	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.4	CRI>80	-	L <sub>70</sub> B <sub>100</sub> >110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	-	-
	Dimensions			
	150mm x 88mm			

Flair	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
<b>L615mm Opal</b>				
FLR-2-2500N-X-MS	1717	22.8	75	4000
	<b>Weight (kg)</b>	<b>CRI</b>	<b>High Temp (°C)</b>	<b>LED Lifetime</b>
	4.4	CRI>80	-	L70B10>110,000h
	<b>Driver lifetime (up to hours)</b>	<b>LED Energy Rating</b>	<b>Emergency Output (Lum/lm)</b>	<b>Nightlight Output (Lum/lm)</b>
	100,000	C	-	-
	<b>Dimensions</b>			
	150mm x 88mm			
FLR-2-3000N-X-MS	1981	26.3	75	4000
	<b>Weight (kg)</b>	<b>CRI</b>	<b>High Temp (°C)</b>	<b>LED Lifetime</b>
	4.4	CRI>80	-	L70B10>110,000h
	<b>Driver lifetime (up to hours)</b>	<b>LED Energy Rating</b>	<b>Emergency Output (Lum/lm)</b>	<b>Nightlight Output (Lum/lm)</b>
	100,000	C	-	-
	<b>Dimensions</b>			
	150mm x 88mm			
FLR-2-1500W-X-MS	1146	15.4	74	3000
	<b>Weight (kg)</b>	<b>CRI</b>	<b>High Temp (°C)</b>	<b>LED Lifetime</b>
	4.4	CRI>80	-	L70B10>100,000h
	<b>Driver lifetime (up to hours)</b>	<b>LED Energy Rating</b>	<b>Emergency Output (Lum/lm)</b>	<b>Nightlight Output (Lum/lm)</b>
	100,000	D	-	-
	<b>Dimensions</b>			
	150mm x 88mm			
FLR-2-2000W-X-MS	1387	18.8	74	3000
	<b>Weight (kg)</b>	<b>CRI</b>	<b>High Temp (°C)</b>	<b>LED Lifetime</b>
	4.4	CRI>80	-	L70B10>100,000h
	<b>Driver lifetime (up to hours)</b>	<b>LED Energy Rating</b>	<b>Emergency Output (Lum/lm)</b>	<b>Nightlight Output (Lum/lm)</b>
	100,000	D	-	-
	<b>Dimensions</b>			
	150mm x 88mm			
FLR-2-2500W-X-MS	1631	22.8	72	3000
	<b>Weight (kg)</b>	<b>CRI</b>	<b>High Temp (°C)</b>	<b>LED Lifetime</b>
	4.4	CRI>80	-	L70B10>100,000h
	<b>Driver lifetime (up to hours)</b>	<b>LED Energy Rating</b>	<b>Emergency Output (Lum/lm)</b>	<b>Nightlight Output (Lum/lm)</b>
	100,000	D	-	-
	<b>Dimensions</b>			
	150mm x 88mm			

Flair	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
<b>L615mm Opal</b>				
FLR-2-3000W-X-MS	1882	26.3	72	3000
	<b>Weight (kg)</b>	<b>CRI</b>	<b>High Temp (°C)</b>	<b>LED Lifetime</b>
	4.4	CRI>80	-	L <sub>70</sub> B <sub>10</sub> >100,000h
	<b>Driver lifetime (up to hours)</b>	<b>LED Energy Rating</b>	<b>Emergency Output (Lum/lm)</b>	<b>Nightlight Output (Lum/lm)</b>
	100,000	D	-	-
	<b>Dimensions</b>			
	150mm x 88mm			
<b>L1215mm Clear</b>				
FLR-4-3000N-P-MS	2153	20.2	106	4000
	<b>Weight (kg)</b>	<b>CRI</b>	<b>High Temp (°C)</b>	<b>LED Lifetime</b>
	7.8	CRI>80	40	L <sub>80</sub> B <sub>10</sub> >72,000h
	<b>Driver lifetime (up to hours)</b>	<b>LED Energy Rating</b>	<b>Emergency Output (Lum/lm)</b>	<b>Nightlight Output (Lum/lm)</b>
	100,000	B	632	-
	<b>Dimensions</b>			
	150mm x 88mm			
FLR-4-4000N-P-MS	2888	27.2	106	4000
	<b>Weight (kg)</b>	<b>CRI</b>	<b>High Temp (°C)</b>	<b>LED Lifetime</b>
	7.8	CRI>80	40	L <sub>80</sub> B <sub>10</sub> >72,000h
	<b>Driver lifetime (up to hours)</b>	<b>LED Energy Rating</b>	<b>Emergency Output (Lum/lm)</b>	<b>Nightlight Output (Lum/lm)</b>
	100,000	B	632	-
	<b>Dimensions</b>			
	150mm x 88mm			
FLR-4-5000N-P-MS	3692	34.8	106	4000
	<b>Weight (kg)</b>	<b>CRI</b>	<b>High Temp (°C)</b>	<b>LED Lifetime</b>
	7.8	CRI>80	40	L <sub>80</sub> B <sub>10</sub> >72,000h
	<b>Driver lifetime (up to hours)</b>	<b>LED Energy Rating</b>	<b>Emergency Output (Lum/lm)</b>	<b>Nightlight Output (Lum/lm)</b>
	100,000	B	632	-
	<b>Dimensions</b>			
	150mm x 88mm			
FLR-4-6000N-P-MS	4778	45.6	105	4000
	<b>Weight (kg)</b>	<b>CRI</b>	<b>High Temp (°C)</b>	<b>LED Lifetime</b>
	7.8	CRI>80	40	L <sub>80</sub> B <sub>10</sub> >72,000h
	<b>Driver lifetime (up to hours)</b>	<b>LED Energy Rating</b>	<b>Emergency Output (Lum/lm)</b>	<b>Nightlight Output (Lum/lm)</b>
	100,000	B	632	-
	<b>Dimensions</b>			
	150mm x 88mm			

Flair	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
<b>L1215mm Clear</b>				
FLR-4-3000W-P-MS	2045	20.2	101	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	7.8	CRI>80	40	L <sub>80</sub> B <sub>100</sub> >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	600	-
	Dimensions			
	150mm x 88mm			
FLR-4-4000W-P-MS	2744	27.2	101	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	7.8	CRI>80	40	L <sub>80</sub> B <sub>100</sub> >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	600	-
	Dimensions			
	150mm x 88mm			
FLR-4-5000W-P-MS	3507	34.8	101	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	7.8	CRI>80	40	L <sub>80</sub> B <sub>100</sub> >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	600	-
	Dimensions			
	150mm x 88mm			
FLR-4-6000W-P-MS	4539	45.6	100	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	7.8	CRI>80	40	L <sub>80</sub> B <sub>100</sub> >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	600	-
	Dimensions			
	150mm x 88mm			
<b>L1215mm Opal</b>				
FLR-4-3000N-X-MS	2250	28.6	79	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	7.8	CRI>80	-	L <sub>70</sub> B <sub>100</sub> >110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	465	-
	Dimensions			
	150mm x 88mm			

Flair	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
<b>L1215mm Opal</b>				
FLR-4-4000N-X-MS	2719	35	78	4000
	<b>Weight (kg)</b>	<b>CRI</b>	<b>High Temp (°C)</b>	<b>LED Lifetime</b>
	7.8	CRI>80	-	L70B10>110,000h
	<b>Driver lifetime (up to hours)</b>	<b>LED Energy Rating</b>	<b>Emergency Output (Lum/lm)</b>	<b>Nightlight Output (Lum/lm)</b>
	100,000	C	465	-
	<b>Dimensions</b>			
	150mm x 88mm			
FLR-4-5000N-X-MS	3168	43.4	73	4000
	<b>Weight (kg)</b>	<b>CRI</b>	<b>High Temp (°C)</b>	<b>LED Lifetime</b>
	7.8	CRI>80	-	L70B10>110,000h
	<b>Driver lifetime (up to hours)</b>	<b>LED Energy Rating</b>	<b>Emergency Output (Lum/lm)</b>	<b>Nightlight Output (Lum/lm)</b>
	100,000	C	465	-
	<b>Dimensions</b>			
	150mm x 88mm			
FLR-4-6000N-X-MS	3575	50.2	71	4000
	<b>Weight (kg)</b>	<b>CRI</b>	<b>High Temp (°C)</b>	<b>LED Lifetime</b>
	7.8	CRI>80	-	L70B10>110,000h
	<b>Driver lifetime (up to hours)</b>	<b>LED Energy Rating</b>	<b>Emergency Output (Lum/lm)</b>	<b>Nightlight Output (Lum/lm)</b>
	100,000	C	465	-
	<b>Dimensions</b>			
	150mm x 88mm			
FLR-4-3000W-X-MS	2138	28.6	75	3000
	<b>Weight (kg)</b>	<b>CRI</b>	<b>High Temp (°C)</b>	<b>LED Lifetime</b>
	7.8	CRI>80	-	L70B10>100,000h
	<b>Driver lifetime (up to hours)</b>	<b>LED Energy Rating</b>	<b>Emergency Output (Lum/lm)</b>	<b>Nightlight Output (Lum/lm)</b>
	100,000	D	441	-
	<b>Dimensions</b>			
	150mm x 88mm			
FLR-4-4000W-X-MS	2583	35	74	3000
	<b>Weight (kg)</b>	<b>CRI</b>	<b>High Temp (°C)</b>	<b>LED Lifetime</b>
	7.8	CRI>80	-	L70B10>100,000h
	<b>Driver lifetime (up to hours)</b>	<b>LED Energy Rating</b>	<b>Emergency Output (Lum/lm)</b>	<b>Nightlight Output (Lum/lm)</b>
	100,000	D	441	-
	<b>Dimensions</b>			
	150mm x 88mm			

Flair	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
<b>L1215mm Opal</b>				
FLR-4-5000W-X-MS	3010	43.4	69	3000
	<b>Weight (kg)</b>	<b>CRI</b>	<b>High Temp (°C)</b>	<b>LED Lifetime</b>
	7.8	CRI>80	-	L70B10>100,000h
	<b>Driver lifetime (up to hours)</b>	<b>LED Energy Rating</b>	<b>Emergency Output (Lum/lm)</b>	<b>Nightlight Output (Lum/lm)</b>
	100,000	D	441	-
	<b>Dimensions</b>			
	150mm x 88mm			
FLR-4-6000W-X-MS	3396	50.2	68	3000
	<b>Weight (kg)</b>	<b>CRI</b>	<b>High Temp (°C)</b>	<b>LED Lifetime</b>
	7.8	CRI>80	-	L70B10>100,000h
	<b>Driver lifetime (up to hours)</b>	<b>LED Energy Rating</b>	<b>Emergency Output (Lum/lm)</b>	<b>Nightlight Output (Lum/lm)</b>
	100,000	D	441	-
	<b>Dimensions</b>			
	150mm x 88mm			
<b>L1515mm Clear</b>				
FLR-5-3750N-P-MS	3549	31.3	113	4000
	<b>Weight (kg)</b>	<b>CRI</b>	<b>High Temp (°C)</b>	<b>LED Lifetime</b>
	9.6	CRI>80	-	L80B10>72,000h
	<b>Driver lifetime (up to hours)</b>	<b>LED Energy Rating</b>	<b>Emergency Output (Lum/lm)</b>	<b>Nightlight Output (Lum/lm)</b>
	100,000	B	628	-
	<b>Dimensions</b>			
	150mm x 88mm			
FLR-5-5000N-P-MS	4535	40.2	113	4000
	<b>Weight (kg)</b>	<b>CRI</b>	<b>High Temp (°C)</b>	<b>LED Lifetime</b>
	9.6	CRI>80	-	L80B10>72,000h
	<b>Driver lifetime (up to hours)</b>	<b>LED Energy Rating</b>	<b>Emergency Output (Lum/lm)</b>	<b>Nightlight Output (Lum/lm)</b>
	100,000	B	628	-
	<b>Dimensions</b>			
	150mm x 88mm			
FLR-5-6250N-P-MS	5525	49.8	111	4000
	<b>Weight (kg)</b>	<b>CRI</b>	<b>High Temp (°C)</b>	<b>LED Lifetime</b>
	9.6	CRI>80	-	L80B10>72,000h
	<b>Driver lifetime (up to hours)</b>	<b>LED Energy Rating</b>	<b>Emergency Output (Lum/lm)</b>	<b>Nightlight Output (Lum/lm)</b>
	100,000	B	628	-
	<b>Dimensions</b>			
	150mm x 88mm			



Flair	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
<b>L1515mm Clear</b>				
FLR-5-7500N-P-MS	6591	61.6	107	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	9.6	CRI>80	-	L <sub>80</sub> B <sub>100</sub> >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	B	628	-
	Dimensions			
	150mm x 88mm			
FLR-5-3750W-P-MS	3372	31.3	108	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	9.6	CRI>80	-	L <sub>80</sub> B <sub>100</sub> >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	596	-
	Dimensions			
	150mm x 88mm			
FLR-5-5000W-P-MS	4308	40.2	107	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	9.6	CRI>80	-	L <sub>80</sub> B <sub>100</sub> >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	596	-
	Dimensions			
	150mm x 88mm			
FLR-5-6250W-P-MS	5249	49.8	105	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	9.6	CRI>80	-	L <sub>80</sub> B <sub>100</sub> >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	596	-
	Dimensions			
	150mm x 88mm			
FLR-5-7500W-P-MS	6261	61.6	102	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	9.6	CRI>80	-	L <sub>80</sub> B <sub>100</sub> >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	596	-
	Dimensions			
	150mm x 88mm			

Flair	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
<b>L1515mm Opal</b>				
FLR-5-3750N-X-MS	2948	33.3	89	4000
	<b>Weight (kg)</b>	<b>CRI</b>	<b>High Temp (°C)</b>	<b>LED Lifetime</b>
	9.6	CRI>80	-	L70B10>110,000h
	<b>Driver lifetime (up to hours)</b>	<b>LED Energy Rating</b>	<b>Emergency Output (Lum/lm)</b>	<b>Nightlight Output (Lum/lm)</b>
	100,000	C	521	-
	<b>Dimensions</b>			
	150mm x 88mm			
FLR-5-5000N-X-MS	3677	41.8	88	4000
	<b>Weight (kg)</b>	<b>CRI</b>	<b>High Temp (°C)</b>	<b>LED Lifetime</b>
	9.6	CRI>80	-	L70B10>110,000h
	<b>Driver lifetime (up to hours)</b>	<b>LED Energy Rating</b>	<b>Emergency Output (Lum/lm)</b>	<b>Nightlight Output (Lum/lm)</b>
	100,000	C	521	-
	<b>Dimensions</b>			
	150mm x 88mm			
FLR-5-6250N-X-MS	4300	51.4	84	4000
	<b>Weight (kg)</b>	<b>CRI</b>	<b>High Temp (°C)</b>	<b>LED Lifetime</b>
	9.6	CRI>80	-	L70B10>110,000h
	<b>Driver lifetime (up to hours)</b>	<b>LED Energy Rating</b>	<b>Emergency Output (Lum/lm)</b>	<b>Nightlight Output (Lum/lm)</b>
	100,000	C	521	-
	<b>Dimensions</b>			
	150mm x 88mm			
FLR-5-7500N-X-MS	4833	59.6	81	4000
	<b>Weight (kg)</b>	<b>CRI</b>	<b>High Temp (°C)</b>	<b>LED Lifetime</b>
	9.6	CRI>80	-	L70B10>110,000h
	<b>Driver lifetime (up to hours)</b>	<b>LED Energy Rating</b>	<b>Emergency Output (Lum/lm)</b>	<b>Nightlight Output (Lum/lm)</b>
	100,000	C	521	-
	<b>Dimensions</b>			
	150mm x 88mm			
FLR-5-3750W-X-MS	2801	33.3	84	3000
	<b>Weight (kg)</b>	<b>CRI</b>	<b>High Temp (°C)</b>	<b>LED Lifetime</b>
	9.6	CRI>80	-	L70B10>100,000h
	<b>Driver lifetime (up to hours)</b>	<b>LED Energy Rating</b>	<b>Emergency Output (Lum/lm)</b>	<b>Nightlight Output (Lum/lm)</b>
	100,000	D	495	-
	<b>Dimensions</b>			
	150mm x 88mm			

Flair	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
<b>L1515mm Opal</b>				
FLR-5-5000W-X-MS	3493	41.8	84	3000
	<b>Weight (kg)</b>	<b>CRI</b>	<b>High Temp (°C)</b>	<b>LED Lifetime</b>
	9.6	CRI>80	-	L70B10>100,000h
	<b>Driver lifetime (up to hours)</b>	<b>LED Energy Rating</b>	<b>Emergency Output (Lum/lm)</b>	<b>Nightlight Output (Lum/lm)</b>
	100,000	D	495	-
	<b>Dimensions</b>			
	150mm x 88mm			
FLR-5-6250W-X-MS	4085	51.4	79	3000
	<b>Weight (kg)</b>	<b>CRI</b>	<b>High Temp (°C)</b>	<b>LED Lifetime</b>
	9.6	CRI>80	-	L70B10>100,000h
	<b>Driver lifetime (up to hours)</b>	<b>LED Energy Rating</b>	<b>Emergency Output (Lum/lm)</b>	<b>Nightlight Output (Lum/lm)</b>
	100,000	D	495	-
	<b>Dimensions</b>			
	150mm x 88mm			
FLR-5-7500W-X-MS	4591	59.6	77	3000
	<b>Weight (kg)</b>	<b>CRI</b>	<b>High Temp (°C)</b>	<b>LED Lifetime</b>
	9.6	CRI>80	-	L70B10>100,000h
	<b>Driver lifetime (up to hours)</b>	<b>LED Energy Rating</b>	<b>Emergency Output (Lum/lm)</b>	<b>Nightlight Output (Lum/lm)</b>
	100,000	D	495	-
	<b>Dimensions</b>			
	150mm x 88mm			

## Fitting Options

Conduit Hole in One End	-1H
Fully Recessed	-R
Conduit Hole in Both Ends	-2H
DALI-2 Dimming / Monitoring	-DA
Switch Dimming	-DI
Maintained Emergency 3 Hour, Self Test	-ES
Central Battery Maintained 110V	-EV
Maintained Emergency 3 Hour, DALI	-ED
Maintained Emergency 3 Hour	-E3
Pure White	-PW
Matt Silver	-MS

- For paint colour options, please replace -MS with required paint code.
- HT Applies for standard version. For any options (e.g.-E3) please check with technical sales.
- -E3 / -ES / -ED options not available on all 615mm versions.
- -R Recessed includes 20mm flange all round. For recessed cut-out add 10mm to width and length shown.
- For 240V changeover relay, please call technical sales on +44 (0)20 8254 2022 to discuss your requirements.

