



Redoubt 90

IP66

IP69

IP69K

IK16 (150J)

Linear

Class I

Surface

Transport

Redoubt 90 is a pit light, specifically designed for heavy duty maintenance pits within rail facilities.

Standard Colours

Stainless Steel Finish

- Product Information

Redoubt 90 has been carefully designed to minimise glare, by restricting the output based on the illuminous surface area, in order to comply with BS-EN 12464-1 (1000lm per 300cm²). Redoubt 90 has been tested to IP69K to ensure cleaning at high pressure and temperature.

Redoubt 90, at 895mm in length, has been constructed in a way that allows for it to be fixed between stanchions. Redoubt 90 provides uniform lighting for both the underside of vehicles and the pit floor, incorporating separate upward and downward illumination. With high levels of impact, ingress and chemical resistance, Redoubt 90 is designed to endure the harsh environments expected within this application.

Rail applications include illuminating sunken, heavy duty maintenance pits within rail maintenance facilities.

Impact Resistance Rating: IK16 (150J). More information, [CLICK HERE](#).

Ingress Protection Rating: IP66, IP69, IP69K. More information, [CLICK HERE](#).

Housing: Marine grade stainless steel body.

Paint: N/A.

Diffuser: Flush clear polycarbonate, with glare reduction film.

Driver: Electronic control gear on a removable tray with fused plug & socket connector block.

Mounting: Wall.

Cable Entry: Supplied with flying lead.

■ **Technical Information**

Redoubt90	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
L895mm				
RDT-3-1400N-SF	1419	12	118	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	12.8	CRI>80	-	L ₉₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	B	327	-
	Dimensions			
	895mm x 281mm x 110mm			
RDT-3-3500N-SF	3442	26.2	131	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	12.8	CRI>80	-	L ₉₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	B	327	-
	Dimensions			
	895mm x 281mm x 110mm			

■ Fitting Options

Microwave Sensor - Intelligent (Basic)	-M5
DALI-2 Dimming / Monitoring	-DA
Emergency Lithium DALI	-EK
Emergency Lithium, Self Test	-EJ
Emergency Lithium	-EL
Stainless Steel Finish	-SF

- Remote control for Intelligent MWS -M5, order code : HRC-05.

