



## FlairMicro

IP67

IK11 (50J)

Linear

Class III

Surface

TM65/66

Community and Public

Transport

FlairMicro is a vandal resistant luminaire specifically designed for community and public applications, as well as transport environments.

### Product Information

FlairMicro's uniform illumination ensures a consistent light distribution, enhancing visibility and reducing glare.

Flair Micro is available in two lumen ranges (900lm and 1500lm per metre) and in various lengths (see technical information section). 24V luminaire with 45° angle adjustable head.

Community and Public applications include the perimeter of buildings. Transport applications include ticket areas, subways and stairs and footbridges.

This luminaire is designed for longevity and sustainability and adheres to our circular design principles. We conduct a circular economy assessment using [TM66](#) and measure embodied carbon (kgCO<sub>2</sub>e) in accordance with [TM65.2](#).

**Impact Resistance Rating:** IK11 (50J). [What is IK Rating?](#)

**Ingress Protection Rating:** IP67. [What is IP Rating?](#)

**Housing:** Extruded aluminium body.

**Paint:** N/A. Silver anodised finish.

**Diffuser:** Opal polyurethane encapsulate.

**Driver:** Remote 24V DC power supply required (Supplied separately).

**Mounting:** Wall or ceiling

**Cable Entry:** Provision for cable entry in remote power supply.

**Design Life:** 30+ years. [What is Design Life?](#)

