



Tuscan 89 Angled S12

IP65

IK08 (5J)

Linear

Class I

Surface

Transport

Tuscan 89 Angled S12 is a vandal resistant luminaire specifically designed in accordance with fire precautions for subsurface rail stations (Section 12).

Standard Colours

Smooth White

Pure White

Textured White

Textured Black

Product Information

Tuscan 89 Angled S12 design directs light precisely where it's needed, reducing wasted illumination and minimising glare. Incorporating a removable gear tray ensures Tuscan 89 Angled S12 is quick and easy to maintain, whilst enabling sustainable technology upgrades.

Tuscan 89 Angled S12 complies with London Underground subsurface standard S1085 utilising low smoke, zero halogen cables and control gear.

Impact Resistance Rating: IK08 (5J). More information, [CLICK HERE](#).

Ingress Protection Rating: IP65. More information, [CLICK HERE](#).

Housing: Zinc coated steel body.

Paint: Polyester powder coat. For all colours available, [CLICK HERE](#).

Diffuser: Frosted toughened glass diffuser in frame secured with tamperproof screws.

Driver: Electronic control gear on removable tray with fused plug & socket connector block.

Mounting: Cornice mounting at either 45° or 30°/60°.

Cable Entry: N/A (Blank body).

■ Technical Information

Tuscan89Angled512	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
L650mm x H145mm x W114mm - 30/60 Degree angle				
D892-2-1500N-F-TB-ST	1507	15.6	97	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	5	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	-	-
	Dimensions			
D892-2-2000N-F-TB-ST	1750	17.5	100	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	5	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	-	-
	Dimensions			
D892-2-2500N-F-TB-ST	1934	20.1	96	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	5	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	-	-
	Dimensions			
D892-2-3000N-F-TB-ST	2282	22.5	101	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	5	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	-	-
	Dimensions			
D892-2-1500W-F-TB-ST	1432	15.6	92	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	5	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	-	-
	Dimensions			

Tuscan89AngledS12	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
L650mm x H145mm x W114mm - 30/60 Degree angle				
D892-2-2000W-F-TB-ST	1663	17.5	95	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	5	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	-	-
	Dimensions			
<hr/>				
D892-2-2500W-F-TB-ST	1837	20.1	91	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	5	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	-	-
	Dimensions			
<hr/>				
D892-2-3000W-F-TB-ST	2168	22.5	96	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	5	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	-	-
	Dimensions			
<hr/>				
L1250mm x H145mm x W114mm - 30/60 Degree angle				
D892-4-2000N-F-TB-ST	2018	20.3	99	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	9.2	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	550	-
	Dimensions			
<hr/>				
D892-4-3000N-F-TB-ST	2485	24.8	100	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	9.2	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	550	-
	Dimensions			

Tuscan89AngledS12	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
L1250mm x H145mm x W114mm - 30/60Degree angle				
D892-4-4000N-F-TB-ST	2964	30.1	98	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	9.2	CRI>80	-	L _e > B ₁₀ > 72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	550	-
	Dimensions			
D892-4-5000N-F-TB-ST	3709	37.1	100	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	9.2	CRI>80	-	L _e > B ₁₀ > 72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	550	-
	Dimensions			
D892-4-6000N-F-TB-ST	3813	39.5	97	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	9.2	CRI>80	-	L _e > B ₁₀ > 72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	550	-
	Dimensions			
D892-4-2000W-F-TB-ST	1917	20.3	94	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	9.2	CRI>80	-	L _e > B ₁₀ > 72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	522	-
	Dimensions			
D892-4-3000W-F-TB-ST	2361	24.8	95	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	9.2	CRI>80	-	L _e > B ₁₀ > 72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	522	-
	Dimensions			

Tuscan89AngledS12	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
L1250mm x H145mm x W114mm - 30/60Degree angle				
D892-4-4000W-F-TB-ST	2816	30.1	94	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	9.2	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	522	-
	Dimensions			
L1250mm x H145mm x W114mm - 30/60Degree angle				
D892-4-5000W-F-TB-ST	3524	37.1	95	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	9.2	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	522	-
	Dimensions			
L1250mm x H145mm x W114mm - 30/60Degree angle				
D892-4-6000W-F-TB-ST	3622	39.5	92	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	9.2	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	522	-
	Dimensions			
L1550mm x H145mm x W114mm - 30/60Degree angle				
D892-5-2500N-F-TB-ST	2669	24.3	110	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	11.2	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	570	-
	Dimensions			
L1550mm x H145mm x W114mm - 30/60Degree angle				
D892-5-3750N-F-TB-ST	3387	30.1	113	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	11.2	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	570	-
	Dimensions			

Tuscan89AngledS12	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
L1550mm x H145mm x W114mm - 30/60Degree angle				
D892-5-5000N-F-TB-ST	4027	36.4	111	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	11.2	CRI>80	-	L _e > B ₁₀ > 72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	570	-
	Dimensions			
D892-5-6250N-F-TB-ST	4666	42.2	111	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	11.2	CRI>80	-	L _e > B ₁₀ > 72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	570	-
	Dimensions			
D892-5-7500N-F-TB-ST	5288	48.5	109	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	11.2	CRI>80	-	L _e > B ₁₀ > 72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	570	-
	Dimensions			
D892-5-2500W-F-TB-ST	2536	24.3	104	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	11.2	CRI>80	-	L _e > B ₁₀ > 72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	541	-
	Dimensions			
D892-5-3750W-F-TB-ST	3218	30.1	107	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	11.2	CRI>80	-	L _e > B ₁₀ > 72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	541	-
	Dimensions			

Tuscan89AngledS12	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
L1550mm x H145mm x W114mm - 30/60Degree angle				
D892-5-5000W-F-TB-ST	3826	36.4	105	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	11.2	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	541	-
	Dimensions			
D892-5-6250W-F-TB-ST	4433	42.2	105	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	11.2	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	541	-
	Dimensions			
D892-5-7500W-F-TB-ST	5024	48.5	104	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	11.2	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	541	-
	Dimensions			
L650mm x H121mm x W121mm - 45 Degree angle				
D893-2-1500N-F-TB-ST	1507	15.6	97	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.7	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	-	-
	Dimensions			
D893-2-2000N-F-TB-ST	1750	17.5	100	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.7	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	-	-
	Dimensions			

Tuscan89AngledS12	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
L650mm x H121mm x W121mm - 45 Degree angle				
D893-2-2500N-F-TB-ST	1934	20.1	96	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.7	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	-	-
	Dimensions			
D893-2-3000N-F-TB-ST	2282	22.5	101	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.7	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	-	-
	Dimensions			
D893-2-1500W-F-TB-ST	1432	15.6	92	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.7	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	-	-
	Dimensions			
D893-2-2000W-F-TB-ST	1663	17.5	95	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.7	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	-	-
	Dimensions			
D893-2-2500W-F-TB-ST	1837	20.1	91	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.7	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	-	-
	Dimensions			

Tuscan89AngledS12	Output (Lum/m)	Load (W)	Efficacy (lm/W)	CCT (K)
L650mm x H121mm x W121mm - 45 Degree angle				
D893-2-3000W-F-TB-ST	2168	22.5	96	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.7	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/m)	Nightlight Output (Lum/m)
	100,000	C	-	-
	Dimensions			
L1250mm x H121mm x W121mm - 45 Degree angle				
D893-4-2000N-F-TB-ST	2018	20.3	99	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	8.7	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/m)	Nightlight Output (Lum/m)
	100,000	C	550	-
	Dimensions			
D893-4-3000N-F-TB-ST	2485	24.8	100	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	8.7	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/m)	Nightlight Output (Lum/m)
	100,000	C	550	-
	Dimensions			
D893-4-4000N-F-TB-ST	2964	30.1	98	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	8.7	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/m)	Nightlight Output (Lum/m)
	100,000	C	550	-
	Dimensions			
D893-4-5000N-F-TB-ST	3709	37.1	100	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	8.7	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/m)	Nightlight Output (Lum/m)
	100,000	C	550	-
	Dimensions			

Tuscan89Angled512	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
L1250mm x H121mm x W121mm - 45 Degree angle				
D893-4-6000N-F-TB-ST	3813	39.5	97	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	8.7	CRI>80	-	L _e > B ₁₀ > 72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	550	-
	Dimensions			
D893-4-2000W-F-TB-ST	1917	20.3	94	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	8.7	CRI>80	-	L _e > B ₁₀ > 72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	522	-
	Dimensions			
D893-4-3000W-F-TB-ST	2361	24.8	95	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	8.7	CRI>80	-	L _e > B ₁₀ > 72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	522	-
	Dimensions			
D893-4-4000W-F-TB-ST	2816	30.1	94	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	8.7	CRI>80	-	L _e > B ₁₀ > 72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	522	-
	Dimensions			
D893-4-5000W-F-TB-ST	3524	37.1	95	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	8.7	CRI>80	-	L _e > B ₁₀ > 72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	522	-
	Dimensions			

Tuscan89AngledS12	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
L1250mm x H121mm x W121mm - 45 Degree angle				
D893-4-6000W-F-TB-ST	3622	39.5	92	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	8.7	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	522	-
	Dimensions			
L1550mm x H121mm x W121mm - 45 Degree angle				
D893-5-2500N-F-TB-ST	2669	24.3	110	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	10.6	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	570	-
	Dimensions			
D893-5-3750N-F-TB-ST	3387	30.1	113	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	10.6	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	570	-
	Dimensions			
D893-5-5000N-F-TB-ST	4027	36.4	111	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	10.6	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	570	-
	Dimensions			
D893-5-6250N-F-TB-ST	4666	42.2	111	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	10.6	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	570	-
	Dimensions			

Tuscan89AngledS12	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
L1550mm x H121mm x W121mm - 45 Degree angle				
D893-5-7500N-F-TB-ST	5288	48.5	109	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	10.6	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	570	-
	Dimensions			
D893-5-2500W-F-TB-ST	2536	24.3	104	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	10.6	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	541	-
	Dimensions			
D893-5-3750W-F-TB-ST	3218	30.1	107	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	10.6	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	541	-
	Dimensions			
D893-5-5000W-F-TB-ST	3826	36.4	105	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	10.6	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	541	-
	Dimensions			
D893-5-6250W-F-TB-ST	4433	42.2	105	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	10.6	CRI>80	-	L ₈₀ B ₁₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	541	-
	Dimensions			

Tuscan89Angled512	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
L1550mm x H121mm x W121mm - 45 Degree angle				
D893-5-7500W-F-TB-ST	5024	48.5	104	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	10.6	CRI>80	-	Le>B>e>72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	541	-
	Dimensions			

Fitting Options

Coastal Paint Finish (Zone 2)	-Z2
Switch Dimming	-DI
DALI-2 Dimming / Monitoring	-DA
Maintained Emergency 3 Hour	-E3
Central Battery Maintained 110V	-EV
Change Over Relay, 240V Relay Supplied	-ER
Maintained Emergency 3 Hour, Self Test	-ES
Maintained Emergency 3 Hour, DALI	-ED
Smooth White	-SW
Pure White	-PW
Textured White	-TW
Textured Black	-TB

- For paint colour options, please replace -TB with required paint code.
- -E3 / -ES / -ED not available on 650mm versions.

