



Arculus Surface

IP65

IK16 (150J)

Modular

Class I

Custodial

Secure Healthcare

Arculus Surface is a ligature resistant luminaire designed for challenging environments including custodial and secure healthcare.

Standard Colours

Matt White

Matt Titanium

Product Information

Arculus Surface's opal diffuser provides a soft lit appearance, while providing a functional light for tasks. The discreet side mounted fixing ensures a clean, unobtrusive aesthetic.

Arculus Surface is designed to meet the requirements of "Design in Mental Health Network's (DiMHN) Testing Guidance for Products in Mental Health Facilities" rating LIG5-5, with a ligature resistant design to help prevent self-harming. It is designed to be disassembled and reinstated to ensure maintenance can be undertaken quickly and easily after anti-pick mastic application.

Secure health applications include corridors and circulation spaces, therapy rooms, communal and exercise areas. Custodial applications include video conferencing, ancillary areas and educational environments.

Impact Resistance Rating: IK16 (150J). More information, [CLICK HERE](#).

Ingress Protection Rating: IP65. More information, [CLICK HERE](#).

Housing: Mild steel body, zinc coated steel frame.

Paint: Polyester powder coat. All colours available, [CLICK HERE](#).

Diffuser: Flush opal polycarbonate diffuser in frame with side mounted tamperproof fixings.

Driver: Electronic control gear on a removable tray for ease of repair/upgrade with fused plug & socket connector block.

Mounting: Ceiling.

Cable Entry: Supplied with flying lead in the back.

■ Technical Information

ArculusSurface	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
Opal				
ARC-2000N-MW	2189	17.5	125	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	14.4	CRI>90	-	L80B10>72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	557	-
	Dimensions			
	628mm x 628mm x 100mm			
ARC-3000N-MW	3190	24.8	129	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	14.4	CRI>90	-	L80B10>72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	557	-
	Dimensions			
	628mm x 628mm x 100mm			
ARC-4000N-MW	4373	34.2	128	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	14.4	CRI>90	-	L80B10>72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	557	-
	Dimensions			
	628mm x 628mm x 100mm			
ARC-2000W-MW	2137	17.6	121	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	14.4	CRI>90	-	L80B10>72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	D	536	-
	Dimensions			
	628mm x 628mm x 100mm			
ARC-3000W-MW	3075	24.9	123	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	14.4	CRI>90	-	L80B10>72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	D	536	-
	Dimensions			
	628mm x 628mm x 100mm			

ArculusSurface	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
Opal				
ARC-4000W-MW	4238	34.4	123	3000
Weight (kg)				
14.4	CRI>90		High Temp (°C)	LED Lifetime
Driver lifetime (up to hours)				
100,000	LED Energy Rating	D	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
Dimensions				
628mm x 628mm x 100mm				

Fitting Options

DALI-2 Dimming / Monitoring	-DA
Maintained Emergency 3 Hour	-E3
Maintained Emergency 3 Hour, Self Test	-ES
Maintained Emergency 3 Hour, DALI	-ED
Matt White	-MW
Matt Titanium	-MT

- For paint colour options, please replace -MW with required paint code.

