

Product Information

Tuscan Wall is designed to provide luminaire spacing of up to nine metres and minimise upward light. Opal LED cover reduces glare whilst providing efficiency. Flush diffuser and frame assembly makes cleaning simple. Hidden, robust wall mounted bracketry for

Community and Public applications include interior communal spaces, as well as the perimeter of buildings. Transport applications include station forecourts.

ease of Mounting and a clean aesthetic.

 $\textbf{Impact Resistance Rating:} \ \mathsf{IK14} \, (\mathsf{100J}). \, \mathsf{More}$

information, $\underline{\text{CLICK HERE}}.$

Ingress Protection Rating: IP65. More information, CLICK HERE.

Housing: Zinc coated steel body.

Paint: Polyester powder coat. For all colours available, CLICK HERE.

Diffuser: Flush clear polycarbonate diffuser in frame secured with tamperproof screws.

Driver: Electronic control gear on removable tray with

fused plug & socket connector block.

Mounting: Wall.

 $\textbf{Cable Entry:} \ \mathsf{Provision} \ \mathsf{for} \ \mathsf{conduit} \ \mathsf{entry} \ \mathsf{in} \ \mathsf{back} \ \mathsf{and}$

ends.

Technical Information

TuscanWall	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	сст (к)
Opal				
TUW-G1-1-800N-MT	887	9.7	91	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	3.5	CRI>80	-	Ls o B1 o > 72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	С	425	-
	Dimensions			
	402mm x 137mm x 147mm			
TUW-G1-1-1100N-MT	1138	12.5	91	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	3.5	CRI>80		Ls o B1 o > 72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	С	425	-
	Dimensions			
	402mm x 137mm x 147mm			
TUW-G1-1-1200N-MT	1283	14.9	86	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	3.5	CRI>80	-	L ₈ ₉ B ₁ ₉ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	С	425	-
	Dimensions			
	402mm x 137mm x 147mm			
TUW-G1-1-800W-MT	843	9.7	87	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	3.5	CRI>80	-	L ₈ ₈ B ₁ ₈ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	С	403	-
	Dimensions			
	402mm x 137mm x 147mm			
TUW-G1-1-1100W-MT	1081	12.5	86	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	3.5	CRI>80	-	L _{8 0} B _{1 0} >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	С	403	
	Dimensions			
	402mm x 137mm x 147mm			

TuscanWall	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	сст (к)
Opal				
TUW-G1-1-1200W-MT	1219	14.9	82	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	3.5	CRI>80	=	L ₈ ₀ B ₁ ₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	С	403	-
	Dimensions			
	402mm x 137mm x 147mm			

Fitting Options

Coastal Paint Finish (Zone 2) Microwave Sensor - Intelligent (Basic) Microwave Sensor - Intelligent (Advanced) Microwave Sensor - Basic -M1 DALI-2 Dimming / Monitoring -DA Non-Maintained 3 Hour Emergency -NE Maintained Emergency 3 Hour, Self Test -ES Maintained Emergency 3 Hour, DALI Matt White -MW Matt Titanium -MT		
Microwave Sensor - Intelligent (Advanced) Microwave Sensor - Basic -M1 DALI-2 Dimming / Monitoring -DA Non-Maintained 3 Hour Emergency -NE Maintained Emergency 3 Hour -E3 Maintained Emergency 3 Hour, Self Test -ES Maintained Emergency 3 Hour, DALI -ED Matt White -MW Matt Titanium -MT	Coastal Paint Finish (Zone 2)	-Z2
Microwave Sensor - Basic -M1 DALI-2 Dimming / Monitoring -DA Non-Maintained 3 Hour Emergency -NE Maintained Emergency 3 Hour -E3 Maintained Emergency 3 Hour, Self Test -ES Maintained Emergency 3 Hour, DALI -ED Matt White -MW Matt Titanium -MT	Microwave Sensor - Intelligent (Basic)	-M5
DALI-2 Dimming / Monitoring -DA Non-Maintained 3 Hour Emergency -NE Maintained Emergency 3 Hour -ES Maintained Emergency 3 Hour, Self Test -ES Maintained Emergency 3 Hour, DALI -ED Matt White -MW Matt Titanium -MT	Microwave Sensor - Intelligent (Advanced)	-M7
Non-Maintained 3 Hour Emergency Maintained Emergency 3 Hour Maintained Emergency 3 Hour, Self Test Maintained Emergency 3 Hour, DALI Matt White -MW Matt Titanium -NE -ES -ES -ES -ED -MT	Microwave Sensor - Basic	-M1
Maintained Emergency 3 Hour, Self Test -ES Maintained Emergency 3 Hour, DALI -ED Matt White -MW Matt Titanium -MT	DALI-2 Dimming / Monitoring	-DA
Maintained Emergency 3 Hour, Self Test -ES Maintained Emergency 3 Hour, DALI -ED Matt White -MW Matt Titanium -MT	Non-Maintained 3 Hour Emergency	-NE
Maintained Emergency 3 Hour, DALI Matt White -MW Matt Titanium -MT	Maintained Emergency 3 Hour	-E3
Matt White -MW Matt Titanium -MT	Maintained Emergency 3 Hour, Self Test	-ES
Matt Titanium -MT	Maintained Emergency 3 Hour, DALI	-ED
	Matt White	-MW
Matt Black .MB	Matt Titanium	-MT
Mall Dlack - Mil	Matt Black	-МВ

- For paint colour options, please replace -MT with required paint code.
- \bullet -M1/-M5/-M7 not available in 1100N version.
- -DA and -M1/-M5/-M7 options cannot be combined.
- Remote control for Intelligent MWS -M5 or -M7, order code : HRC-11.





