



Terminus Wall

IP65

IK11 (50J)

Downlights

Class I

Surface

HT40°C

Community and Public

Transport

Terminus Wall is a vandal resistant luminaire specifically designed for transport applications and community and public installations.

Standard Colours

Matt White

Matt Titanium

Matt Silver

Product Information

Terminus Wall's uniform illumination ensures a consistent light distribution, enhancing visibility and reducing glare. Incorporating a removable gear tray ensures Terminus Wall is quick and easy to maintain, whilst enabling sustainable technology upgrades. Community and Public applications include the exterior and perimeter of buildings. Transport applications include station forecourts.

Impact Resistance Rating: IK11 (50J). More information, [CLICK HERE](#).

Ingress Protection Rating: IP65. More information, [CLICK HERE](#).

Housing: Extruded and die cast aluminium body.

Paint: Polyester power coat. For all colours available, [CLICK HERE](#).

Diffuser: Clear polycarbonate diffuser.

Driver: Integral electronic control gear with terminal box.

Mounting: Wall.

Cable Entry: Provision for cable entry into terminal box.

Technical Information

TerminusWall	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
Wide Beam				
TMW-1100NW-C-MT	966	8.3	117	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.5	CRI>80	40	L ₈₀ B ₁₀₀ >60,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	544	-
	Dimensions			
	Ø184mm, 290mm, 275mm			

TerminusWall	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
Wide Beam				
TMW-2000NW-C-MT	1674	14.2	118	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.5	CRI>80	40	L _{80B10} >60,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	544	-
	Dimensions			
	Ø184mm, 290mm, 275mm			
TMW-3000NW-C-MT	2367	19.8	119	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.5	CRI>80	40	L _{80B10} >60,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	544	-
	Dimensions			
	Ø184mm, 290mm, 275mm			
TMW-4500NW-C-MT	3635	31.2	116	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.5	CRI>80	40	L _{80B10} >60,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	544	-
	Dimensions			
	Ø184mm, 290mm, 275mm			
TMW-1100WW-C-MT	918	8.3	111	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.5	CRI>80	40	L _{80B10} >60,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	516	-
	Dimensions			
	Ø184mm, 290mm, 275mm			
TMW-2000WW-C-MT	1590	14.2	112	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.5	CRI>80	40	L _{80B10} >60,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	516	-
	Dimensions			
	Ø184mm, 290mm, 275mm			

TerminusWall	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
Wide Beam				
TMW-3000WW-C-MT	2249	19.8	114	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.5	CRI>80	40	L ₈₀ B ₁₀ >60,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	516	-
	Dimensions			
	Ø184mm, 290mm, 275mm			
TMW-4500WW-C-MT	3453	31.2	111	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.5	CRI>80	40	L ₈₀ B ₁₀ >60,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	516	-
	Dimensions			
	Ø184mm, 290mm, 275mm			
Medium Beam				
TMW-1100NM-C-MT	943	8.2	115	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.5	CRI>80	40	L ₈₀ B ₁₀ >60,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	527	-
	Dimensions			
	Ø184mm, 290mm, 275mm			
TMW-2000NM-C-MT	1664	14.2	117	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.5	CRI>80	40	L ₈₀ B ₁₀ >60,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	527	-
	Dimensions			
	Ø184mm, 290mm, 275mm			
TMW-3000NM-C-MT	2332	20.1	116	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.5	CRI>80	40	L ₈₀ B ₁₀ >60,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	527	-
	Dimensions			
	Ø184mm, 290mm, 275mm			

TerminusWall	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
Medium Beam				
TMW-4500NM-C-MT	3511	31.2	113	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.5	CRI>80	40	L ₈₀ B ₁₀ >60,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	527	-
	Dimensions			
	Ø184mm, 290mm, 275mm			
TMW-1100WM-C-MT	896	8.2	109	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.5	CRI>80	40	L ₈₀ B ₁₀ >60,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	500	-
	Dimensions			
	Ø184mm, 290mm, 275mm			
TMW-2000WM-C-MT	1581	14.2	111	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.5	CRI>80	40	L ₈₀ B ₁₀ >60,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	500	-
	Dimensions			
	Ø184mm, 290mm, 275mm			
TMW-3000WM-C-MT	2215	20.1	110	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.5	CRI>80	40	L ₈₀ B ₁₀ >60,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	500	-
	Dimensions			
	Ø184mm, 290mm, 275mm			
TMW-4500WM-C-MT	3335	31.2	107	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.5	CRI>80	40	L ₈₀ B ₁₀ >60,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	500	-
	Dimensions			
	Ø184mm, 290mm, 275mm			

TerminusWall	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
Wide Up/Down				
TMWD-1100NW-C-MT	966/966 (Down/Up)	8.3/8.3 (Down/Up)	117	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.5	CRI>80	-	L ₈₀ B ₁₀ >60,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	544	-
	Dimensions			
	Ø184mm, 290mm, 275mm			
TMWD-2000NW-C-MT	1674/966 (Down/Up)	14.2/8.3 (Down/Up)	118	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.5	CRI>80	-	L ₈₀ B ₁₀ >60,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	544	-
	Dimensions			
	Ø184mm, 290mm, 275mm			
TMWD-1100WW-C-MT	918/918 (Down/Up)	8.3/8.3 (Down/Up)	111	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.5	CRI>80	-	L ₈₀ B ₁₀ >60,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	516	-
	Dimensions			
	Ø184mm, 290mm, 275mm			
TMWD-2000WW-C-MT	1590/918 (Down/Up)	14.2/8.3 (Down/Up)	112	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.5	CRI>80	-	L ₈₀ B ₁₀ >60,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	516	-
	Dimensions			
	Ø184mm, 290mm, 275mm			
Medium Up/Down				
TMWD-1100NM-C-MT	943/943 (Down/Up)	8.2/8.2 (Down/Up)	115	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.5	CRI>80	-	L ₈₀ B ₁₀ >60,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	527	-
	Dimensions			
	Ø184mm, 290mm, 275mm			

TerminusWall	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
Medium Up/Down				
TMWD-2000NM-C-MT	1664/943 (Down/UP)	14.2/8.2 (Down/Up)	117	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.5	CRI>80	-	L ₈₀ B ₁₀ >60,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	527	-
	Dimensions			
	Ø184mm, 290mm, 275mm			
TMWD-1100WM-C-MT	896/896 (Down/Up)	8.2/8.2 (Down/Up)	109	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.5	CRI>80	-	L ₈₀ B ₁₀ >60,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	500	-
	Dimensions			
	Ø184mm, 290mm, 275mm			
TMWD-2000WM-C-MT	1581/896 (Down/Up)	14.2/8.2 (Down/Up)	111	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.5	CRI>80	-	L ₈₀ B ₁₀ >60,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	500	-
	Dimensions			
	Ø184mm, 290mm, 275mm			

Fitting Options

DALI-2 Dimming / Monitoring	-DA
Central Battery Maintained 110V	-EV
Maintained Emergency 3 Hour in Remote Box	-EB
Change Over Relay, 240V Relay Supplied	-ER
Matt White	-MW
Matt Titanium	-MT
Matt Silver	-MS

- For paint colour options, please replace -MT with required paint code.
- HT Applies to standard version. For any options (e.g. -E3), please check with technical sales.
- For Post Top version, please contact technical sales on +44 (0)20 8254 2022 or email technical@designplan.co.uk.
- Upward light only available on 1100lm and 2000lm versions.
- For -EB option, please note that remote box is IP65 rated.

