



Flair Angled

IP65

IK16 (150J)

Linear

Class I

Surface

TM65/66

Community and Public

Transport

Flair Angled is a vandal resistant luminaire designed specifically for challenging environments, such as transport applications and community and public installations.

Standard Colours

Pure White

Matt Silver

Product Information

Flair Angled directs light where it's needed, reducing wasted illumination and minimising glare.

Incorporating a removable gear tray ensures Flair Angled is quick and easy to maintain, whilst enabling sustainable technology upgrades.

Transport applications include ticket areas, station forecourts, general circulation areas, covered platforms and stairs and footbridges. Community and public applications include subways.

This luminaire is designed for longevity and sustainability and adheres to our circular design principles. We conduct a circular economy assessment using [TM66](#) and measure embodied carbon (kgCO₂e) in accordance with [TM65.2](#).

Impact Resistance Rating: IK16 (150J). [Learn More.](#)

Ingress Protection Rating: IP65. [Learn More.](#)

Housing: Zinc coated steel body.

Paint: Polyester powder coat. [All Colour Options Available Here.](#)

Diffuser: Clear polycarbonate diffuser in frame secured with tamperproof screws. Internal reflective louvre with opal liner.

Driver: Electronic control gear on removable tray for ease of repair/upgrade with fused plug & socket connector block.

Mounting: Wall

Cable Entry: Provision for conduit entry in back.

Design Life: 30+ years. [Learn More.](#)

■ Technical Information

| FlairAngled | Output (Lum/lm) | Load (W) | Efficacy (lm/W) | CCT (K) |
|---------------------|--------------------------------------|--------------------------|----------------------------------|-----------------------------------|
| L615mm Clear | | | | |
| FLRA-2-1500N-P-MS | 1064 | 11.5 | 92 | 4000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 3.6 | CRI>80 | - | L80B10>72,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | B | - | - |
| | Dimensions | | | |
| | 150mm x 110mm | | | |
| FLRA-2-2000N-P-MS | 1421 | 15 | 95 | 4000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 3.6 | CRI>80 | - | L80B10>72,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | B | - | - |
| | Dimensions | | | |
| | 150mm x 110mm | | | |
| FLRA-2-2500N-P-MS | 1779 | 18.7 | 95 | 4000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 3.6 | CRI>80 | - | L80B10>72,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | B | - | - |
| | Dimensions | | | |
| | 150mm x 110mm | | | |
| FLRA-2-3000N-P-MS | 2234 | 23.6 | 94 | 4000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 3.6 | CRI>80 | - | L80B10>72,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | B | - | - |
| | Dimensions | | | |
| | 150mm x 110mm | | | |
| FLRA-2-1500W-P-MS | 1011 | 11.5 | 88 | 3000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 3.6 | CRI>80 | - | L80B10>72,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | C | - | - |
| | Dimensions | | | |
| | 150mm x 110mm | | | |

| FlairAngled | Output (Lum/lm) | Load (W) | Efficacy (lm/W) | CCT (K) |
|---------------------|--------------------------------------|--------------------------|----------------------------------|--|
| L615mm Clear | | | | |
| FLRA-2-2000W-P-MS | 1350 | 15 | 90 | 3000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 3.6 | CRI>80 | - | L ₈₀ B ₁₀₀ >72,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | C | - | - |
| | Dimensions | | | |
| | 150mm x 110mm | | | |
| FLRA-2-2500W-P-MS | 1690 | 18.7 | 90 | 3000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 3.6 | CRI>80 | - | L ₈₀ B ₁₀₀ >72,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | C | - | - |
| | Dimensions | | | |
| | 150mm x 110mm | | | |
| FLRA-2-3000W-P-MS | 2122 | 23.6 | 90 | 3000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 3.6 | CRI>80 | - | L ₈₀ B ₁₀₀ >72,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | C | - | - |
| | Dimensions | | | |
| | 150mm x 110mm | | | |
| L615mm Opal | | | | |
| FLRA-2-1500N-X-MS | 1206 | 15.4 | 78 | 4000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 3.6 | CRI>80 | - | L ₇₀ B ₁₀₀ >110,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | C | - | - |
| | Dimensions | | | |
| | 150mm x 110mm | | | |
| FLRA-2-2000N-X-MS | 1460 | 18.8 | 78 | 4000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 3.6 | CRI>80 | - | L ₇₀ B ₁₀₀ >110,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | C | - | - |
| | Dimensions | | | |
| | 150mm x 110mm | | | |

| FlairAngled | Output (Lum/lm) | Load (W) | Efficacy (lm/W) | CCT (K) |
|--------------------|--------------------------------------|--------------------------|----------------------------------|-----------------------------------|
| L615mm Opal | | | | |
| FLRA-2-2500N-X-MS | 1717 | 22.8 | 75 | 4000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 3.6 | CRI>80 | - | L70B10>110,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | C | - | - |
| | Dimensions | | | |
| | 150mm x 110mm | | | |
| FLRA-2-3000N-X-MS | 1981 | 26.3 | 75 | 4000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 3.6 | CRI>80 | - | L70B10>110,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | C | - | - |
| | Dimensions | | | |
| | 150mm x 110mm | | | |
| FLRA-2-1500W-X-MS | 1146 | 15.4 | 74 | 3000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 3.6 | CRI>80 | - | L70B10>100,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | D | - | - |
| | Dimensions | | | |
| | 150mm x 110mm | | | |
| FLRA-2-2000W-X-MS | 1387 | 18.8 | 74 | 3000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 3.6 | CRI>80 | - | L70B10>100,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | D | - | - |
| | Dimensions | | | |
| | 150mm x 110mm | | | |
| FLRA-2-2500W-X-MS | 1631 | 22.8 | 72 | 3000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 3.6 | CRI>80 | - | L70B10>100,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | D | - | - |
| | Dimensions | | | |
| | 150mm x 110mm | | | |

| FlairAngled | Output (Lum/lm) | Load (W) | Efficacy (lm/W) | CCT (K) |
|----------------------|--------------------------------------|--------------------------|----------------------------------|-----------------------------------|
| L615mm Opal | | | | |
| FLRA-2-3000W-X-MS | 1882 | 26.3 | 72 | 3000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 3.6 | CRI>80 | - | L70B100>100,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | D | - | - |
| | Dimensions | | | |
| | 150mm x 110mm | | | |
| L1215mm Clear | | | | |
| FLRA-4-3000N-P-MS | 2153 | 20.2 | 106 | 4000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 6.7 | CRI>80 | 40 | L80B100>72,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | B | 632 | - |
| | Dimensions | | | |
| | 150mm x 110mm | | | |
| FLRA-4-4000N-P-MS | 2888 | 27.2 | 106 | 4000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 6.7 | CRI>80 | 40 | L80B100>72,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | B | 632 | - |
| | Dimensions | | | |
| | 150mm x 110mm | | | |
| FLRA-4-5000N-P-MS | 3692 | 34.8 | 106 | 4000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 6.7 | CRI>80 | 40 | L80B100>72,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | B | 632 | - |
| | Dimensions | | | |
| | 150mm x 110mm | | | |
| FLRA-4-6000N-P-MS | 4778 | 45.6 | 105 | 4000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 6.7 | CRI>80 | 40 | L80B100>72,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | B | 632 | - |
| | Dimensions | | | |
| | 150mm x 110mm | | | |

| FlairAngled | Output (Lum/lm) | Load (W) | Efficacy (lm/W) | CCT (K) |
|----------------------|--------------------------------------|--------------------------|----------------------------------|--|
| L1215mm Clear | | | | |
| FLRA-4-3000W-P-MS | 2045 | 20.2 | 101 | 3000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 6.7 | CRI>80 | 40 | L ₈₀ B ₁₀₀ >72,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | C | 600 | - |
| | Dimensions | | | |
| | 150mm x 110mm | | | |
| FLRA-4-4000W-P-MS | 2744 | 27.2 | 101 | 3000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 6.7 | CRI>80 | 40 | L ₈₀ B ₁₀₀ >72,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | C | 600 | - |
| | Dimensions | | | |
| | 150mm x 110mm | | | |
| FLRA-4-5000W-P-MS | 3507 | 34.8 | 101 | 3000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 6.7 | CRI>80 | 40 | L ₈₀ B ₁₀₀ >72,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | C | 600 | - |
| | Dimensions | | | |
| | 150mm x 110mm | | | |
| FLRA-4-6000W-P-MS | 4539 | 45.6 | 100 | 3000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 6.7 | CRI>80 | 40 | L ₈₀ B ₁₀₀ >72,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | C | 600 | - |
| | Dimensions | | | |
| | 150mm x 110mm | | | |
| L1215mm Opal | | | | |
| FLRA-4-3000N-X-MS | 2250 | 28.6 | 79 | 4000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 6.7 | CRI>80 | - | L ₇₀ B ₁₀₀ >110,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | C | 465 | - |
| | Dimensions | | | |
| | 150mm x 110mm | | | |

| FlairAngled | Output (Lum/lm) | Load (W) | Efficacy (lm/W) | CCT (K) |
|---------------------|--------------------------------------|--------------------------|----------------------------------|-----------------------------------|
| L1215mm Opal | | | | |
| FLRA-4-4000N-X-MS | 2719 | 35 | 78 | 4000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 6.7 | CRI>80 | - | L70B10>110,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | C | 465 | - |
| | Dimensions | | | |
| | 150mm x 110mm | | | |
| FLRA-4-5000N-X-MS | 3168 | 43.4 | 73 | 4000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 6.7 | CRI>80 | - | L70B10>110,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | C | 465 | - |
| | Dimensions | | | |
| | 150mm x 110mm | | | |
| FLRA-4-6000N-X-MS | 3575 | 50.2 | 71 | 4000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 6.7 | CRI>80 | - | L70B10>110,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | C | 465 | - |
| | Dimensions | | | |
| | 150mm x 110mm | | | |
| FLRA-4-3000W-X-MS | 2138 | 28.6 | 75 | 3000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 6.7 | CRI>80 | - | L70B10>100,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | D | 441 | - |
| | Dimensions | | | |
| | 150mm x 110mm | | | |
| FLRA-4-4000W-X-MS | 2583 | 35 | 74 | 3000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 6.7 | CRI>80 | - | L70B10>100,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | D | 441 | - |
| | Dimensions | | | |
| | 150mm x 110mm | | | |

| FlairAngled | Output (Lum/lm) | Load (W) | Efficacy (lm/W) | CCT (K) |
|----------------------|--------------------------------------|--------------------------|----------------------------------|-----------------------------------|
| L1215mm Opal | | | | |
| FLRA-4-5000W-X-MS | 3010 | 43.4 | 69 | 3000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 6.7 | CRI>80 | - | L70B50>100,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | D | 441 | - |
| | Dimensions | | | |
| | 150mm x 110mm | | | |
| FLRA-4-6000W-X-MS | 3396 | 50.2 | 68 | 3000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 6.7 | CRI>80 | - | L70B50>100,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | D | 441 | - |
| | Dimensions | | | |
| | 150mm x 110mm | | | |
| L1515mm Clear | | | | |
| FLRA-5-3750N-P-MS | 3549 | 31.3 | 113 | 4000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 8.2 | CRI>80 | - | L80B50>72,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | B | 628 | - |
| | Dimensions | | | |
| | 150mm x 110mm | | | |
| FLRA-5-5000N-P-MS | 4535 | 40.2 | 113 | 4000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 8.2 | CRI>80 | - | L80B50>72,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | B | 628 | - |
| | Dimensions | | | |
| | 150mm x 110mm | | | |
| FLRA-5-6250N-P-MS | 5525 | 49.8 | 111 | 4000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 8.2 | CRI>80 | - | L80B50>72,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | B | 628 | - |
| | Dimensions | | | |
| | 150mm x 110mm | | | |

| FlairAngled | Output (Lum/lm) | Load (W) | Efficacy (lm/W) | CCT (K) |
|----------------------|--------------------------------------|--------------------------|----------------------------------|-----------------------------------|
| L1515mm Clear | | | | |
| FLRA-5-7500N-P-MS | 6591 | 61.6 | 107 | 4000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 8.2 | CRI>80 | - | L80B10>72,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | B | 628 | - |
| | Dimensions | | | |
| | 150mm x 110mm | | | |
| FLRA-5-3750W-P-MS | 3372 | 31.3 | 108 | 3000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 8.2 | CRI>80 | - | L80B10>72,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | C | 596 | - |
| | Dimensions | | | |
| | 150mm x 110mm | | | |
| FLRA-5-5000W-P-MS | 4308 | 40.2 | 107 | 3000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 8.2 | CRI>80 | - | L80B10>72,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | C | 596 | - |
| | Dimensions | | | |
| | 150mm x 110mm | | | |
| FLRA-5-6250W-P-MS | 5249 | 49.8 | 105 | 3000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 8.2 | CRI>80 | - | L80B10>72,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | C | 596 | - |
| | Dimensions | | | |
| | 150mm x 110mm | | | |
| FLRA-5-7500W-P-MS | 6261 | 61.6 | 102 | 3000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 8.2 | CRI>80 | - | L80B10>72,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | C | 596 | - |
| | Dimensions | | | |
| | 150mm x 110mm | | | |

| FlairAngled | Output (Lum/lm) | Load (W) | Efficacy (lm/W) | CCT (K) |
|---------------------|--------------------------------------|--------------------------|----------------------------------|-----------------------------------|
| L1515mm Opal | | | | |
| FLRA-5-3750N-X-MS | 2948 | 33.3 | 89 | 4000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 8.2 | CRI>80 | - | L70B10>110,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | C | 521 | - |
| | Dimensions | | | |
| | 150mm x 110mm | | | |
| FLRA-5-5000N-X-MS | 3677 | 41.8 | 88 | 4000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 8.2 | CRI>80 | - | L70B10>110,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | C | 521 | - |
| | Dimensions | | | |
| | 150mm x 110mm | | | |
| FLRA-5-6250N-X-MS | 4300 | 51.4 | 84 | 4000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 8.2 | CRI>80 | - | L70B10>110,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | C | 521 | - |
| | Dimensions | | | |
| | 150mm x 110mm | | | |
| FLRA-5-7500N-X-MS | 4833 | 59.6 | 81 | 4000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 8.2 | CRI>80 | - | L70B10>110,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | C | 521 | - |
| | Dimensions | | | |
| | 150mm x 110mm | | | |
| FLRA-5-3750W-X-MS | 2801 | 33.3 | 84 | 3000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 8.2 | CRI>80 | - | L70B10>100,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | D | 495 | - |
| | Dimensions | | | |
| | 150mm x 110mm | | | |

| FlairAngled | Output (Lum/Im) | Load (W) | Efficacy (lm/W) | CCT (K) |
|---------------------|--------------------------------------|--------------------------|----------------------------------|-----------------------------------|
| L1515mm Opal | | | | |
| FLRA-5-5000W-X-MS | 3493 | 41.8 | 84 | 3000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 8.2 | CRI>80 | - | L70B10>100,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/Im) | Nightlight Output (Lum/Im) |
| | 100,000 | D | 495 | - |
| | Dimensions | | | |
| | 150mm x 110mm | | | |
| FLRA-5-6250W-X-MS | 4085 | 51.4 | 79 | 3000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 8.2 | CRI>80 | - | L70B10>100,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/Im) | Nightlight Output (Lum/Im) |
| | 100,000 | D | 495 | - |
| | Dimensions | | | |
| | 150mm x 110mm | | | |
| FLRA-5-7500W-X-MS | 4591 | 59.6 | 77 | 3000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 8.2 | CRI>80 | - | L70B10>100,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/Im) | Nightlight Output (Lum/Im) |
| | 100,000 | D | 495 | - |
| | Dimensions | | | |
| | 150mm x 110mm | | | |

Fitting Options

| | |
|--|-----|
| Conduit Hole in One End | -1H |
| Conduit Hole in Both Ends | -2H |
| Switch Dimming | -DI |
| DALI-2 Dimming / Monitoring | -DA |
| Maintained Emergency 3 Hour | -E3 |
| Central Battery Maintained 110V | -EV |
| Maintained Emergency 3 Hour, Self Test | -ES |
| Maintained Emergency 3 Hour, DALI | -ED |
| Pure White | -PW |
| Matt Silver | -MS |

- For paint colour options, please replace -MS with required paint code.
- -E3 / -ES / -ED options not available on all 615mm versions.
- -DA and -DI options are not available on all 615mm versions.
- For 240V changeover relay, please call technical sales on +44 (0)20 8254 2022 to discuss your requirements.

