



Tuscan II

IP65

IK16 (150J)

Bulkhead

Class I

Surface

Community and Public

Transport

Tuscan II is a vandal resistant bulkhead specifically designed for transport applications and community and public installations.

Standard Colours

Textured White

Textured Black

Matt Titanium

Product Information

Tuscan II's opal diffuser provides a soft lit appearance, while providing uniform illumination, ensuring a consistent light distribution. Incorporating a removable gear tray ensures Tuscan II is quick and easy to maintain, whilst enabling sustainable technology upgrades.

Community and Public applications include the exterior of buildings. Transport applications include open platforms, covered platforms, station forecourts, stations and foot bridges.

This luminaire is designed for longevity and sustainability and adheres to our circular design principles. We conduct a circular economy assessment using [TM66](#) and measure embodied carbon (kgCO₂e) in accordance with [TM65.2](#).

Impact Resistance Rating: IK16 (150J). [Learn More.](#)

Ingress Protection Rating: IP65. [Learn More.](#)

Housing: Zinc coated steel body.

Paint: Polyester powder coat. [All Colour Options Available Here.](#)

Diffuser: Opal polycarbonate diffuser in frame secured with tamperproof screws.

Driver: Electronic control gear on removable tray for ease of repair/upgrade with fused plug & socket connector block.

Mounting: Wall or cornice.

Cable Entry: Provision for conduit entry in back and ends.

Design Life: 30+ years. [Learn More.](#)

■ **Technical Information**

| TuscanII | Output (Lum/lm) | Load (W) | Efficacy (lm/W) | CCT (K) |
|-----------------|--------------------------------------|--------------------------|----------------------------------|-----------------------------------|
| Opal | | | | |
| D864-2000N-X-TB | 1756 | 20.4 | 86 | 4000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 4.2 | CRI>80 | - | L70B10>110,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | C | 376 | - |
| | Dimensions | | | |
| | 400mm x 237mm x 175mm | | | |
| D864-3000N-X-TB | 2438 | 29.8 | 82 | 4000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 4.2 | CRI>80 | - | L70B10>110,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | C | 376 | - |
| | Dimensions | | | |
| | 400mm x 237mm x 175mm | | | |
| D864-2000W-X-TB | 1668 | 20.4 | 82 | 3000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 4.2 | CRI>80 | - | L70B10>100,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | D | 357 | - |
| | Dimensions | | | |
| | 400mm x 237mm x 175mm | | | |
| D864-3000W-X-TB | 2316 | 29.8 | 78 | 3000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 4.2 | CRI>80 | - | L70B10>100,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | D | 357 | - |
| | Dimensions | | | |
| | 400mm x 237mm x 175mm | | | |

Fitting Options

| | |
|--|-----|
| Anti-Graffiti Diffuser Coating | -AG |
| Coastal Paint Finish (Zone 2) | -Z2 |
| Blank Ends | -BE |
| Network Rail Specs | -NT |
| DALI-2 Dimming / Monitoring | -DA |
| Non-Maintained 3 Hour Emergency | -NE |
| Maintained Emergency 3 Hour | -E3 |
| Central Battery Maintained 110V | -EV |
| Change Over Relay, 240V Relay Supplied | -ER |
| Textured White | -TW |
| Textured Black | -TB |
| Matt Titanium | -MT |

- For paint colour options, please replace -TB with required paint code.
- -NE cannot be combined with -DA.

