



Tuscan II

IP65

IK16 (150J)

Linear

Class I

Surface

Community and Public

Transport

Tuscan II is a vandal resistant bulkhead specifically designed for transport applications and community and public installations.

Standard Colours

Textured White

Textured Black

Matt Titanium

Product Information

Tuscan II's opal diffuser provides a soft lit appearance, while providing uniform illumination, ensuring a consistent light distribution. Incorporating a removable gear tray ensures Tuscan II is quick and easy to maintain, whilst enabling sustainable technology upgrades.

Community and Public applications include the exterior of buildings. Transport applications include open platforms, covered platforms, station forecourts, stations and foot bridges.

Impact Resistance Rating: IK16 (150J). More information, [CLICK HERE](#).

Ingress Protection Rating: IP65. More information, [CLICK HERE](#).

Housing: Zinc coated steel body.

Paint: Polyester powder coat. For all colours available, [CLICK HERE](#).

Diffuser: Opal polycarbonate diffuser in frame secured with tamperproof screws.

Driver: Electronic control gear on removable tray with fused plug & socket connector block.

Mounting: Wall or cornice.

Cable Entry: Provision for conduit entry in back and ends.

■ **Technical Information**

TuscanII	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
Opal				
D864-2000N-X-TB	1756	20.4	86	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.2	CRI>80	-	L70B10>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	376	-
	Dimensions			
	400mm x 237mm x 175mm			
D864-3000N-X-TB	2438	29.8	82	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.2	CRI>80	-	L70B10>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	376	-
	Dimensions			
	400mm x 237mm x 175mm			
D864-2000W-X-TB	1668	20.4	82	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.2	CRI>80	-	L70B10>100,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	D	357	-
	Dimensions			
	400mm x 237mm x 175mm			
D864-3000W-X-TB	2316	29.8	78	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	4.2	CRI>80	-	L70B10>100,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	D	357	-
	Dimensions			
	400mm x 237mm x 175mm			

■ Fitting Options

Anti-Graffiti Diffuser Coating	-AG
Coastal Paint Finish (Zone 2)	-Z2
Blank Ends	-BE
Network Rail Specs	-NT
DALI-2 Dimming / Monitoring	-DA
Non-Maintained 3 Hour Emergency	-NE
Maintained Emergency 3 Hour	-E3
Central Battery Maintained 110V	-EV
Change Over Relay, 240V Relay Supplied	-ER
Textured White	-TW
Textured Black	-TB
Matt Titanium	-MT

- For paint colour options, please replace -TB with required paint code.

