



## Torino G2

IP21

IK11 (50J)

Bulkhead

Class I

Surface

Community and Public

Transport

Torino G2 is a vandal resistant bulkhead specifically designed for transport applications and community and public installations.

Standard Colours

Matt White

Matt Silver

### Product Information

Torino G2's opal diffuser provides a soft lit appearance, while providing uniform illumination, ensuring a consistent light distribution. Incorporating a removable gear tray ensures Torino G2 is quick and easy to maintain, whilst enabling sustainable technology upgrades.

Transport applications include office and back of house. Community and Public applications include the interior communal spaces of buildings.

This luminaire is designed for longevity and sustainability and adheres to our circular design principles. We conduct a circular economy assessment using [TM66](#) and measure embodied carbon (kgCO<sub>2</sub>e) in accordance with [TM65.2](#).

**Impact Resistance Rating:** IK11 (50J). [Learn More.](#)

**Ingress Protection Rating:** IP21. [Learn More.](#)

**Housing:** Zinc coated steel body and trim.

**Paint:** Polyester powder coat. [All Colour Options Available Here.](#)

**Diffuser:** Opal polycarbonate diffuser with trim secured with tamperproof screws.

**Driver:** Electronic control gear on removable tray for ease of repair/upgrade with fused plug & socket connector block.

**Mounting:** Wall or ceiling

**Cable Entry:** Provision for conduit entry in back.

**Design Life:** 30+ years. [Learn More.](#)

■ **Technical Information**

TorinoG2	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
<b>Opal</b>				
TOR-G2-1500N-MW	1589	14.5	109	4000
	<b>Weight (kg)</b>	<b>CRI</b>	<b>High Temp (°C)</b>	<b>LED Lifetime</b>
	2.3	CRI>80	-	L70B10>110,000h
	<b>Driver lifetime (up to hours)</b>	<b>LED Energy Rating</b>	<b>Emergency Output (Lum/lm)</b>	<b>Nightlight Output (Lum/lm)</b>
	100,000	C	394	-
	<b>Dimensions</b>			
	Ø420mm, 100mm			
TOR-G2-2100N-MW	2227	20.4	109	4000
	<b>Weight (kg)</b>	<b>CRI</b>	<b>High Temp (°C)</b>	<b>LED Lifetime</b>
	2.3	CRI>80	-	L70B10>110,000h
	<b>Driver lifetime (up to hours)</b>	<b>LED Energy Rating</b>	<b>Emergency Output (Lum/lm)</b>	<b>Nightlight Output (Lum/lm)</b>
	100,000	C	394	-
	<b>Dimensions</b>			
	Ø420mm, 100mm			
TOR-G2-2500N-MW	2655	24.3	109	4000
	<b>Weight (kg)</b>	<b>CRI</b>	<b>High Temp (°C)</b>	<b>LED Lifetime</b>
	2.3	CRI>80	-	L70B10>110,000h
	<b>Driver lifetime (up to hours)</b>	<b>LED Energy Rating</b>	<b>Emergency Output (Lum/lm)</b>	<b>Nightlight Output (Lum/lm)</b>
	100,000	C	394	-
	<b>Dimensions</b>			
	Ø420mm, 100mm			

## Fitting Options

Microwave Sensor - Basic	-M1
DALI-2 Dimming / Monitoring	-DA
Switch Dimming	-DI
Central Battery Maintained 110V	-EV
Maintained Emergency 3 Hour	-E3
Matt White	-MW
Matt Silver	-MS
Corridor Function	-CF

- For paint colour options, please replace -MW with required paint code.
- -CF will only work if combined with -M1 or an external presence detection sensor supplied by others.
- -DA / -DI and -M1 options cannot be combined.
- For 240V changeover relay option, please call technical sales on +44 (0)20 8254 2022 to discuss your requirements.

