

Bedhead AL is a ligature resistant bulkhead designed for challenging environments including secure healthcare facilities.



Product Information

Bedhead AL provides focused illumination at a downward 45° angle to create a soothing ambiance for reading and relaxation. For added comfort and convenience, it is adjustable at a 25° rotation in either direction.

Bedhead AL minimises the risk of self-harm or injury by preventing the attachment of ligatures. It is designed to be disassembled and reinstated to ensure maintenance can be undertaken quickly and easily after anti-pick mastic application.

Applications include Bedrooms and En-Suites.

Impact Resistance Rating: IK10 (20J). More information, <u>CLICK HERE</u>. Ingress Protection Rating: IP20. More information, <u>CLICK HERE</u>.

Housing: Aluminium body.

Paint: Polyester powder coat. All colours available,

CLICK HERE.

Diffuser: Clear polycarbonate diffuser.Driver: Integral electronic control gear.Mounting: Wall.Cable Entry: In back. Supplied with flying lead and


connectors.


Technical Information

BedheadAL	Output (Lum/Im)	Load (W)	Efficacy (lm/W)	сст (к)
Clear				
BH2-300W-SW	270	3.9	70	2700
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	1	CRI>80	-	L ₇₀ B ₁₀ >110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/Im)	Nightlight Output (Lum/lm)
	100,000	D	-	-
	Dimensions			
	Ø168mm, 83mm			

Fitting Options

Switch Dimming	 -DI
Smooth White	-SW





Tel: 020 8254 2000 | Fax: 020 8644 4253 | Email: sales@designplan.co.uk | Web: designplan.co.uk Designplan Lighting Ltd. 16 Kimpton Park Way, Sutton, Surrey, United Kingdom, SM3 9QS | Registered in England No. 784246