



Gemini Metro

IP54

IK08 (5J)

Bulkhead

Class I

Surface

Transport

Gemini Metro is an S12 bulkhead specifically designed in accordance with fire precautions for subsurface rail stations (Section 12).

Standard Colours

Textured White

Product Information

Gemini Metro provides robust ambient lighting, featuring a removable gear tray for easy maintenance and sustainable technology upgrades. Gemini Metro complies with London Underground subsurface standard S1085 utilising low smoke, zero halogen cables and control gear.

Impact Resistance Rating: IK08 (5J). More information, [CLICK HERE](#).

Ingress Protection Rating: IP54. More information, [CLICK HERE](#).

Housing: Zinc coated steel body.

Paint: Polyester powder coat. All colours available, [CLICK HERE](#).

Diffuser: Frosted toughened glass diffuser secured with tamperproof screws.

Driver: Electronic control gear on removable tray with fused plug & socket connector block.

Mounting: Wall.

Cable Entry: Provision for conduit entry in back and ends.

Additional Information: Available with exit legends to ISO 7010.

▪ **Technical Information**

GeminiMetro	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
Glass				
M1977-LEDN-F-TW-ST	398	5	82	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	2.3	CRI>80	-	L _{80B10} >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	60	-
	Dimensions			
	366mm x 133mm x 90mm			

■ Fitting Options

Exit Legend - Running Man, Arrow Up	-R1
Exit Legend - Running Man, Arrow Right	-R3
Exit Legend - Running Man, Arrow Down/Left	-R6
Exit Legend - Running Man, Arrow Up/Right	-R2
Coastal Paint Finish (Zone 2)	-Z2
Exit Legend - Running Man, Arrow Down/Right	-R4
Exit Legend - Running Man, Arrow Left	-R7
Exit Legend - Running Man, Arrow Down	-R5
Non-Maintained 3 Hour Emergency	-NE
Maintained Emergency 3 Hour	-E3
Central Battery Maintained 110V	-EV
Change Over Relay, 240V Relay Supplied	-ER
Textured White	-TW

- -R5 not compliant with ISO 16069/BS 5499-4.
- Emergency Output 60lm with legend.
- Version for secure healthcare and anti-ligature available. Please contact technical sales on 020 8254 2022 or email technical@designplan.co.uk

