



Tuscan 88 Angled

IP65

IK16 (150J)

Linear

Class I

Surface

Community and Public

Custodial

Transport

Tuscan 88 Angled is a vandal resistant luminaire specifically designed for challenging environments, such as custodial facilities, transport applications and community and public installations.

Standard Colours

Textured White

Textured Black

Matt Titanium

Product Information

Tuscan 88 Angled directs light precisely where it's needed, reducing wasted illumination and minimising glare. Incorporating a removable gear tray ensures Tuscan 88 Angled is quick and easy to maintain, whilst enabling sustainable technology upgrades.

Community and Public applications include subways, car parks, and the perimeter of buildings. Custodial applications include police stations, law courts and association areas. Transport applications include covered platforms, general circulation, back of house, stairs and footbridges.

This luminaire is designed for longevity and sustainability and adheres to our circular design principles. We conduct a circular economy assessment using [TM66](#) and measure embodied carbon (kgCO₂e) in accordance with [TM65.2](#).

Impact Resistance Rating: IK16 (150J). [Learn More.](#)

Ingress Protection Rating: IP65. [Learn More.](#)

Housing: Zinc coated steel body.

Paint: Polyester powder coat. [All Colour Options Available Here.](#)

Diffuser: Opal polycarbonate diffuser in frame secured with tamperproof screws.

Driver: Electronic control gear on removable tray for ease of repair/upgrade with fused plug & socket connector block.

Mounting: Cornice mounting at either 45° or 30°/60°.

Cable Entry: Provision for conduit entry in back and ends.

Design Life: 30+ years. [Learn More.](#)

▪ **Technical Information**

Tuscan88Angled	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
L700mm x H188mm x W139mm - 30/60 Degree angle				
D882-2-1500N-X-TB	1377	15.6	88	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	6	CRI>80	-	L70000>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	457	-
	Dimensions			
D882-2-2000N-X-TB	1801	20.8	87	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	6	CRI>80	-	L70000>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	457	-
	Dimensions			
D882-2-2500N-X-TB	2297	26.8	86	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	6	CRI>80	-	L70000>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	457	-
	Dimensions			
D882-2-3000N-X-TB	2567	30.8	83	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	6	CRI>80	-	L70000>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	457	-
	Dimensions			
D882-2-1500W-X-TB	1308	15.6	84	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	6	CRI>80	-	L70000>100,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	D	434	-
	Dimensions			

Tuscan88Angled	Output (Lum/m)	Load (W)	Efficacy (lm/W)	CCT (K)
L700mm x H188mm x W139mm - 30/60 Degree angle				
D882-2-2000W-X-TB	1711	20.8	82	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	6	CRI>80	-	L70B100>100,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/m)	Nightlight Output (Lum/m)
	100,000	D	434	-
	Dimensions			
<hr/>				
D882-2-2500W-X-TB	2182	26.8	81	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	6	CRI>80	-	L70B100>100,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/m)	Nightlight Output (Lum/m)
	100,000	D	434	-
	Dimensions			
<hr/>				
D882-2-3000W-X-TB	2439	30.8	79	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	6	CRI>80	-	L70B100>100,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/m)	Nightlight Output (Lum/m)
	100,000	D	434	-
	Dimensions			
<hr/>				
L1300mm x H188mm x W139mm - 30/60 Degree angle				
D882-4-3000N-X-TB	2804	28.4	99	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	10.6	CRI>80	-	L70B100>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/m)	Nightlight Output (Lum/m)
	100,000	C	638	-
	Dimensions			
<hr/>				
D882-4-4000N-X-TB	3718	38.8	96	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	10.6	CRI>80	-	L70B100>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/m)	Nightlight Output (Lum/m)
	100,000	C	638	-
	Dimensions			

Tuscan88Angled	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
L1300mm x H188mm x W139mm - 30/60Degree angle				
D882-4-5000N-X-TB	4616	50.3	92	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	10.6	CRI>80	-	L70B10>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	638	-
	Dimensions			
D882-4-6000N-X-TB	5298	58.4	91	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	10.6	CRI>80	-	L70B10>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	638	-
	Dimensions			
D882-4-3000W-X-TB	2664	28.4	94	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	10.6	CRI>80	-	L70B10>100,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	D	606	-
	Dimensions			
D882-4-4000W-X-TB	3532	38.8	91	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	10.6	CRI>80	-	L70B10>100,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	D	606	-
	Dimensions			
D882-4-5000W-X-TB	4385	50.3	87	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	10.6	CRI>80	-	L70B10>100,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	D	606	-
	Dimensions			

Tuscan88Angled	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
L1300mm x H188mm x W139mm - 30/60Degree angle				
D882-4-6000W-X-TB	5033	58.4	86	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	10.6	CRI>80	-	L70B10>100,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	D	606	-
	Dimensions			
L1600mm x H188mm x W139mm - 30/60Degree angle				
D882-5-3750N-X-TB	3565	34.8	102	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	12.4	CRI>80	-	L70B10>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	588	-
	Dimensions			
D882-5-5000N-X-TB	4681	47.6	98	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	12.4	CRI>80	-	L70B10>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	588	-
	Dimensions			
D882-5-6250N-X-TB	5860	62.5	94	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	12.4	CRI>80	-	L70B10>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	588	-
	Dimensions			
D882-5-7500N-X-TB	6520	72.1	90	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	12.4	CRI>80	-	L70B10>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	588	-
	Dimensions			

Tuscan88Angled	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
L1600mm x H188mm x W139mm - 30/60 Degree angle				
D882-5-3750W-X-TB	3387	34.8	97	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	12.4	CRI>80	-	L70B10>100,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	D	558	-
	Dimensions			
<hr/>				
D882-5-5000W-X-TB	4447	47.6	93	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	12.4	CRI>80	-	L70B10>100,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	D	558	-
	Dimensions			
<hr/>				
D882-5-6250W-X-TB	5567	62.5	89	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	12.4	CRI>80	-	L70B10>100,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	D	558	-
	Dimensions			
<hr/>				
D882-5-7500W-X-TB	6194	72.1	86	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	12.4	CRI>80	-	L70B10>100,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	D	558	-
	Dimensions			
<hr/>				
L700mm x H158mm x W158mm - 45 Degree angle				
D883-2-1500N-X-TB	1377	15.6	88	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	5.7	CRI>80	-	L70B10>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	457	-
	Dimensions			

Tuscan88Angled	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
L700mm x H158mm x W158mm - 45 Degree angle				
D883-2-2000N-X-TB	1801	20.8	87	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	5.7	CRI>80	-	L70B100>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	457	-
	Dimensions			
<hr/>				
D883-2-2500N-X-TB	2297	26.8	86	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	5.7	CRI>80	-	L70B100>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	457	-
	Dimensions			
<hr/>				
D883-2-3000N-X-TB	2567	30.8	83	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	5.7	CRI>80	-	L70B100>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	457	-
	Dimensions			
<hr/>				
D883-2-1500W-X-TB	1308	15.6	84	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	5.7	CRI>80	-	L70B100>100,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	D	434	-
	Dimensions			
<hr/>				
D883-2-2000W-X-TB	1711	20.8	82	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	5.7	CRI>80	-	L70B100>100,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	D	434	-
	Dimensions			

Tuscan88Angled	Output (Lum/m)	Load (W)	Efficacy (lm/W)	CCT (K)
L700mm x H158mm x W158mm - 45 Degree angle				
D883-2-2500W-X-TB	2182	26.8	81	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	5.7	CRI>80	-	L70B100>100,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/m)	Nightlight Output (Lum/m)
	100,000	D	434	-
	Dimensions			
L700mm x H158mm x W158mm - 45 Degree angle				
D883-2-3000W-X-TB	2439	30.8	79	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	5.7	CRI>80	-	L70B100>100,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/m)	Nightlight Output (Lum/m)
	100,000	D	434	-
	Dimensions			
L1300mm x H158mm x W158mm - 45 Degree angle				
D883-4-3000N-X-TB	2804	28.4	99	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	10.1	CRI>80	-	L70B100>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/m)	Nightlight Output (Lum/m)
	100,000	C	638	-
	Dimensions			
L1300mm x H158mm x W158mm - 45 Degree angle				
D883-4-4000N-X-TB	3718	38.8	96	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	10.1	CRI>80	-	L70B100>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/m)	Nightlight Output (Lum/m)
	100,000	C	638	-
	Dimensions			
L1300mm x H158mm x W158mm - 45 Degree angle				
D883-4-5000N-X-TB	4616	50.3	92	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	10.1	CRI>80	-	L70B100>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/m)	Nightlight Output (Lum/m)
	100,000	C	638	-
	Dimensions			

Tuscan88Angled	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
L1300mm x H158mm x W158mm - 45 Degree angle				
D883-4-6000N-X-TB	5298	58.4	91	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	10.1	CRI>80	-	L70B10>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	638	-
	Dimensions			
D883-4-3000W-X-TB	2664	28.4	94	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	10.1	CRI>80	-	L70B10>100,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	D	606	-
	Dimensions			
D883-4-4000W-X-TB	3532	38.8	91	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	10.1	CRI>80	-	L70B10>100,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	D	606	-
	Dimensions			
D883-4-5000W-X-TB	4385	50.3	87	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	10.1	CRI>80	-	L70B10>100,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	D	606	-
	Dimensions			
D883-4-6000W-X-TB	5033	58.4	86	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	10.1	CRI>80	-	L70B10>100,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	D	606	-
	Dimensions			

Tuscan88Angled	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
L1600mm x H158mm x W158mm - 45 Degree angle				
D883-5-3750N-X-TB	3565	34.8	102	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	11.5	CRI>80	-	L70B10>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	588	-
	Dimensions			
<hr/>				
D883-5-5000N-X-TB	4681	47.6	98	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	11.5	CRI>80	-	L70B10>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	588	-
	Dimensions			
<hr/>				
D883-5-6250N-X-TB	5860	62.5	94	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	11.5	CRI>80	-	L70B10>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	588	-
	Dimensions			
<hr/>				
D883-5-7500N-X-TB	6520	72.1	90	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	11.5	CRI>80	-	L70B10>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	588	-
	Dimensions			
<hr/>				
D883-5-3750W-X-TB	3387	34.8	97	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	11.5	CRI>80	-	L70B10>100,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	D	558	-
	Dimensions			

Tuscan88Angled	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
L1600mm x H158mm x W158mm - 45 Degree angle				
D883-5-5000W-X-TB	4447	47.6	93	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	11.5	CRI>80	-	L70B10>100,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	D	558	-
	Dimensions			
<hr/>				
D883-5-6250W-X-TB	5567	62.5	89	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	11.5	CRI>80	-	L70B10>100,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	D	558	-
	Dimensions			
<hr/>				
D883-5-7500W-X-TB	6194	72.1	86	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	11.5	CRI>80	-	L70B10>100,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	D	558	-
	Dimensions			

Fitting Options

Anti-Graffiti Diffuser Coating	-AG
Coastal Paint Finish (Zone 2)	-Z2
Blank Ends	-BE
Network Rail Specs	-NT
Switch Dimming	-DI
DALI-2 Dimming / Monitoring	-DA
Maintained Emergency 3 Hour	-E3
Central Battery Maintained 110V	-EV
Change Over Relay, 240V Relay Supplied	-ER
Maintained Emergency 3 Hour, Self Test	-ES
Maintained Emergency 3 Hour, DALI	-ED
Textured White	-TW
Textured Black	-TB
Matt Titanium	-MT

- For paint colour options, please replace -TB with required paint code.
- -ED not available on all 700mm versions.

