



Gateline

IP65

IK14 (100J)

Bulkhead

Class I

Surface

Custodial

Gateline is a "defined emergency escape route" light specifically designed for challenging environments, such as custodial facilities.

Standard Colours

Matt White

Textured Black

Matt Titanium

Product Information

Gateline is designed specifically to provide a uniform and consistent illumination of 15 lux at a working plane of 1.0m, based on a maximum mounting height of 3.8m, to ensure compliance with specific emergency lighting requirements in custodial environments. Applications include emergency lighting for ancillary areas.

Impact Resistance Rating: IK14 (100J). More information, [CLICK HERE](#).

Ingress Protection Rating: IP65. More information, [CLICK HERE](#).

Housing: Zinc coated steel body.

Paint: Polyester powder coat. All colours available, [CLICK HERE](#).

Diffuser: Clear polycarbonate diffuser in frame secured with tamperproof screws.

Driver: Integral 3h non-maintained emergency module and battery.

Mounting: Wall. Ceiling and other mounting versions are available on request, please contact Technical Sales on +44 (0)20 8254 2022 or e-mail technicalsales@designplan.co.uk

Cable Entry: Provision for conduit entry in back and ends.

■ Technical Information

| Gateline | Output (Lum/lm) | Load (W) | Efficacy (lm/W) | CCT (K) |
|--------------------------------------|-----------------------|---------------------|---------------------------|------------------------------------------|
| Opal | | | | |
| ODL-G1-1-LEDN-MT-BR-NE | N/A | 6W in charging mode | - | 4000 |
| Weight (kg) | | | | |
| | 3.5 | CRI>80 | - | L ₈₀ B ₅₀ >72,000h |
| Driver lifetime (up to hours) | | | | |
| | 100,000 | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | | C | 534 | - |
| Dimensions | | | | |
| | 402mm x 148mm x 137mm | | | |
| ODL-G1-1-LEDW-MT-BR-NE | N/A | 6W in charging mode | - | 3000 |
| Weight (kg) | | | | |
| | 3.5 | CRI>80 | - | L ₈₀ B ₅₀ >72,000h |
| Driver lifetime (up to hours) | | | | |
| | 100,000 | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | | C | 507 | - |
| Dimensions | | | | |
| | 402mm x 148mm x 137mm | | | |

■ Fitting Options

| | |
|--------------------------------------------|-----|
| Non-Maintained 3 Hour Emergency, Self Test | -NS |
| Non-Maintained 3 Hour Emergency, DALI | -ND |
| Matt White | -MW |
| Textured Black | -TB |
| Matt Titanium | -MT |

- For paint colour options, please replace -MT with required paint code.
- Remove suffix -BR for Non External Bracket Version.

