



Gateline

IP65

IK14 (100J)

Bulkhead

Class I

Surface

TM65/66

Custodial

Gateline is a "defined emergency escape route" light specifically designed for challenging environments, such as custodial facilities.

Standard Colours

Textured Black

Matt White

Matt Titanium

■ Product Information

Gateline is designed to deliver uniform illumination of 15 lux at a working plane of 1.0m, with a maximum mounting height of 3.8m. This ensures compliance with stringent emergency lighting requirements in custodial environments, providing reliable illumination for defined emergency escape routes. Applications include wall mounted emergency lighting for ancillary areas. Ceiling and other mounting versions are available on request, please contact Technical Sales on 020 8254 2022 to discuss your requirements.

This luminaire is designed for longevity and sustainability and adheres to our circular design principles. We conduct a circular economy assessment using [TM66](#) and measure embodied carbon (kgCO₂e) in accordance with [TM65.2](#).

Impact Resistance Rating: IK14 (100J). [What is IK Rating?](#)

Ingress Protection Rating: IP65. [What is IP Rating?](#)

Housing: Zinc coated steel body.

Paint: Polyester powder coat. [All Colour Options Available Here.](#)

Diffuser: Clear polycarbonate diffuser in frame secured with tamperproof screws.

Driver: Integral 3h non-maintained emergency module and battery.

Mounting: Wall.

Cable Entry: Provision for conduit entry in back and ends.

Design Life: 30+ years. [What is Design Life?](#)

■ Technical Information

| Gateline | Output (Lum/lm) | Load (W) | Efficacy (lm/W) | CCT (K) |
|------------------------|-------------------------------|---------------------|---------------------------|----------------------------|
| Opal | | | | |
| ODL-G1-1-LEDN-MT-BR-NE | N/A | 6W in charging mode | - | 4000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 3.5 | CRI>80 | - | Life > 72,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | B | 534 | - |
| Dimensions | | | | |
| 402mm x 148mm x 137mm | | | | |
| ODL-G1-1-LEDW-MT-BR-NE | N/A | 6W in charging mode | - | 3000 |
| | Weight (kg) | CRI | High Temp (°C) | LED Lifetime |
| | 3.5 | CRI>80 | - | Life > 72,000h |
| | Driver lifetime (up to hours) | LED Energy Rating | Emergency Output (Lum/lm) | Nightlight Output (Lum/lm) |
| | 100,000 | C | 507 | - |
| Dimensions | | | | |
| 402mm x 148mm x 137mm | | | | |

■ Fitting Options

| | |
|--------------------------------------------|-----|
| Non-Maintained 3 Hour Emergency, DALI | -ND |
| Non-Maintained 3 Hour Emergency, Self Test | -NS |
| Textured Black | -TB |
| Matt White | -MW |
| Matt Titanium | -MT |

- For paint colour options, please replace -MT with required paint code.
- Remove suffix -BR for Non External Bracket Version.

