



Cove Mini

IP54

IK11 (50J)

Linear

Class I

Surface

Custodial

Secure Healthcare

Cove Mini is a vandal resistant luminaire specifically designed for challenging environments including secure healthcare and custodial facilities.

Standard Colours

Matt White

Matt Silver

- Product Information

Cove Mini's angled design directs light precisely where it's needed, reducing wasted illumination and minimising glare. Incorporating a removable gear tray ensures Cove Mini is quick and easy to maintain, whilst enabling sustainable technology upgrades. Applications include nurse stations and back of house.

Impact Resistance Rating: IK11 (50J). More information, [CLICK HERE](#).

Ingress Protection Rating: IP54. More information, [CLICK HERE](#).

Housing: Zinc coated steel body and die-cast aluminium end caps with tamperproof screws.

Paint: Polyester powder coat. All colours available, [CLICK HERE](#).

Diffuser: Clip-in opal polycarbonate diffuser.

Driver: Integral electronic control gear.

Mounting: Wall.

Cable Entry: Provision for conduit entry in back.

■ Technical Information

CoveMini	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
L616mm				
D966-2-1250N-X-MS	1097	10.2	107	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	1.7	CRI>80	-	L ₈₀ B ₁₀₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	-	-
	Dimensions			
	95mm x 95mm			
D966-2-1500N-X-MS	1252	11.4	109	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	1.7	CRI>80	-	L ₈₀ B ₁₀₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	-	-
	Dimensions			
	95mm x 95mm			
D966-2-1250W-X-MS	1046	10.2	103	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	1.7	CRI>80	-	L ₈₀ B ₁₀₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	-	-
	Dimensions			
	95mm x 95mm			
D966-2-1500W-X-MS	1193	11.4	105	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	1.7	CRI>80	-	L ₈₀ B ₁₀₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	-	-
	Dimensions			
	95mm x 95mm			
L1222mm				
D966-4-2500N-X-MS	2129	17.7	120	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	3.7	CRI>80	-	L ₈₀ B ₁₀₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	-	-
	Dimensions			
	95mm x 95mm			

CoveMini	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
L1222mm				
D966-4-3000N-X-MS	2741	22.5	121	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	3.7	CRI>80	-	L ₈₀ B ₅₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	-	-
	Dimensions			
	95mm x 95mm			
D966-4-2500W-X-MS	2029	17.7	115	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	3.7	CRI>80	-	L ₈₀ B ₅₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	-	-
	Dimensions			
	95mm x 95mm			
D966-4-3000W-X-MS	2613	22.5	116	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	3.7	CRI>80	-	L ₈₀ B ₅₀ >72,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	-	-
	Dimensions			
	95mm x 95mm			

Fitting Options

Switch Dimming	-DI
DALI-2 Dimming / Monitoring	-DA
Matt White	-MW
Matt Silver	-MS

- For paint colour options, please replace -MS with required paint code.

