



## Cove Mini

IP54

IK11 (50J)

Linear

Class I

Surface

Custodial

Secure Healthcare

Cove Mini is a vandal resistant luminaire specifically designed for challenging environments including secure healthcare and custodial facilities.

Standard Colours

Matt White

Matt Silver

### - Product Information

Cove Mini's angled design directs light precisely where it's needed, reducing wasted illumination and minimising glare. Incorporating a removable gear tray ensures Cove Mini is quick and easy to maintain, whilst enabling sustainable technology upgrades. Applications include nurse stations and back of house.

**Impact Resistance Rating:** IK11 (50J). More information, [CLICK HERE](#).

**Ingress Protection Rating:** IP54. More information, [CLICK HERE](#).

**Housing:** Zinc coated steel body and die-cast aluminium end caps with tamperproof screws.

**Paint:** Polyester powder coat. All colours available, [CLICK HERE](#).

**Diffuser:** Clip-in opal polycarbonate diffuser.

**Driver:** Integral electronic control gear.

**Mounting:** Wall.

**Cable Entry:** Provision for conduit entry in back.

## ■ Technical Information

| CoveMini          | Output (Lum/Im)                      | Load (W)                 | Efficacy (lm/W)                  | CCT (K)                           |
|-------------------|--------------------------------------|--------------------------|----------------------------------|-----------------------------------|
| <b>L616mm</b>     |                                      |                          |                                  |                                   |
| D966-2-1250N-X-MS | 1097                                 | 10.2                     | 107                              | 4000                              |
|                   | <b>Weight (kg)</b>                   | <b>CRI</b>               | <b>High Temp (°C)</b>            | <b>LED Lifetime</b>               |
|                   | 1.7                                  | CRI>80                   | -                                | L80B10>72,000h                    |
|                   | <b>Driver lifetime (up to hours)</b> | <b>LED Energy Rating</b> | <b>Emergency Output (Lum/Im)</b> | <b>Nightlight Output (Lum/Im)</b> |
|                   | 100,000                              | C                        | -                                | -                                 |
|                   | <b>Dimensions</b>                    |                          |                                  |                                   |
|                   | 95mm x 95mm                          |                          |                                  |                                   |
| D966-2-1500N-X-MS | 1252                                 | 11.4                     | 109                              | 4000                              |
|                   | <b>Weight (kg)</b>                   | <b>CRI</b>               | <b>High Temp (°C)</b>            | <b>LED Lifetime</b>               |
|                   | 1.7                                  | CRI>80                   | -                                | L80B10>72,000h                    |
|                   | <b>Driver lifetime (up to hours)</b> | <b>LED Energy Rating</b> | <b>Emergency Output (Lum/Im)</b> | <b>Nightlight Output (Lum/Im)</b> |
|                   | 100,000                              | C                        | -                                | -                                 |
|                   | <b>Dimensions</b>                    |                          |                                  |                                   |
|                   | 95mm x 95mm                          |                          |                                  |                                   |
| D966-2-1250W-X-MS | 1046                                 | 10.2                     | 103                              | 3000                              |
|                   | <b>Weight (kg)</b>                   | <b>CRI</b>               | <b>High Temp (°C)</b>            | <b>LED Lifetime</b>               |
|                   | 1.7                                  | CRI>80                   | -                                | L80B10>72,000h                    |
|                   | <b>Driver lifetime (up to hours)</b> | <b>LED Energy Rating</b> | <b>Emergency Output (Lum/Im)</b> | <b>Nightlight Output (Lum/Im)</b> |
|                   | 100,000                              | C                        | -                                | -                                 |
|                   | <b>Dimensions</b>                    |                          |                                  |                                   |
|                   | 95mm x 95mm                          |                          |                                  |                                   |
| D966-2-1500W-X-MS | 1193                                 | 11.4                     | 105                              | 3000                              |
|                   | <b>Weight (kg)</b>                   | <b>CRI</b>               | <b>High Temp (°C)</b>            | <b>LED Lifetime</b>               |
|                   | 1.7                                  | CRI>80                   | -                                | L80B10>72,000h                    |
|                   | <b>Driver lifetime (up to hours)</b> | <b>LED Energy Rating</b> | <b>Emergency Output (Lum/Im)</b> | <b>Nightlight Output (Lum/Im)</b> |
|                   | 100,000                              | C                        | -                                | -                                 |
|                   | <b>Dimensions</b>                    |                          |                                  |                                   |
|                   | 95mm x 95mm                          |                          |                                  |                                   |
| <b>L1222mm</b>    |                                      |                          |                                  |                                   |
| D966-4-2500N-X-MS | 2129                                 | 17.7                     | 120                              | 4000                              |
|                   | <b>Weight (kg)</b>                   | <b>CRI</b>               | <b>High Temp (°C)</b>            | <b>LED Lifetime</b>               |
|                   | 3.7                                  | CRI>80                   | -                                | L80B10>72,000h                    |
|                   | <b>Driver lifetime (up to hours)</b> | <b>LED Energy Rating</b> | <b>Emergency Output (Lum/Im)</b> | <b>Nightlight Output (Lum/Im)</b> |
|                   | 100,000                              | C                        | -                                | -                                 |
|                   | <b>Dimensions</b>                    |                          |                                  |                                   |
|                   | 95mm x 95mm                          |                          |                                  |                                   |

| CoveMini          | Output (Lum/lm)                      | Load (W)                 | Efficacy (lm/W)                  | CCT (K)                                   |
|-------------------|--------------------------------------|--------------------------|----------------------------------|---|
| <b>L1222mm</b>    |                                      |                          |                                  |   |
| D966-4-3000N-X-MS | 2741                                 | 22.5                     | 121                              | 4000                                      |
|                   | <b>Weight (kg)</b>                   | <b>CRI</b>               | <b>High Temp (°C)</b>            | <b>LED Lifetime</b>                       |
|                   | 3.7                                  | CRI>80                   | -                                | L <sub>80</sub> B <sub>100</sub> >72,000h |
|                   | <b>Driver lifetime (up to hours)</b> | <b>LED Energy Rating</b> | <b>Emergency Output (Lum/lm)</b> | <b>Nightlight Output (Lum/lm)</b>         |
|                   | 100,000                              | C                        | -                                | -   |
|                   | <b>Dimensions</b>                    |                          |                                  |   |
|                   | 95mm x 95mm                          |                          |                                  |   |
| D966-4-2500W-X-MS | 2029                                 | 17.7                     | 115                              | 3000                                      |
|                   | <b>Weight (kg)</b>                   | <b>CRI</b>               | <b>High Temp (°C)</b>            | <b>LED Lifetime</b>                       |
|                   | 3.7                                  | CRI>80                   | -                                | L <sub>80</sub> B <sub>100</sub> >72,000h |
|                   | <b>Driver lifetime (up to hours)</b> | <b>LED Energy Rating</b> | <b>Emergency Output (Lum/lm)</b> | <b>Nightlight Output (Lum/lm)</b>         |
|                   | 100,000                              | C                        | -                                | -   |
|                   | <b>Dimensions</b>                    |                          |                                  |   |
|                   | 95mm x 95mm                          |                          |                                  |   |
| D966-4-3000W-X-MS | 2613                                 | 22.5                     | 116                              | 3000                                      |
|                   | <b>Weight (kg)</b>                   | <b>CRI</b>               | <b>High Temp (°C)</b>            | <b>LED Lifetime</b>                       |
|                   | 3.7                                  | CRI>80                   | -                                | L <sub>80</sub> B <sub>100</sub> >72,000h |
|                   | <b>Driver lifetime (up to hours)</b> | <b>LED Energy Rating</b> | <b>Emergency Output (Lum/lm)</b> | <b>Nightlight Output (Lum/lm)</b>         |
|                   | 100,000                              | C                        | -                                | -   |
|                   | <b>Dimensions</b>                    |                          |                                  |   |
|                   | 95mm x 95mm                          |                          |                                  |   |

## Fitting Options

|                             |     |
|-----------------------------|-----|
| Switch Dimming              | -DI |
| DALI-2 Dimming / Monitoring | -DA |
| Matt White                  | -MW |
| Matt Silver                 | -MS |

- For paint colour options, please replace -MS with required paint code.

