



Tuscan Angled Class II



Transport

Tuscan Angled Class II is a vandal resistant luminaire specifically designed for transport applications.

Standard Colours

Textured Black

Textured White

Product Information

Tuscan Angled Class II directs light where it's needed, reducing wasted illumination and minimising glare.

Incorporating a removable gear tray ensures Tuscan Angled Class II is quick and easy to maintain, whilst enabling sustainable technology upgrades.

This luminaire is designed for longevity and sustainability and adheres to our circular design principles. We conduct a circular economy assessment using [TM66](#) and measure embodied carbon (kgCO₂e) in accordance with [TM65.2](#).

Impact Resistance Rating: IK16 (150J). [What is IK Rating?](#)

Ingress Protection Rating: IP65. [What is IP Rating?](#)

Housing: Zinc coated steel body.

Paint: Polyester powder coat. [All Colour Options Available Here.](#)

Diffuser: Opal polycarbonate diffuser in frame secured with tamperproof screws.

Driver: Electronic control gear on removable tray for ease of repair/upgrade.

Mounting: Cornice mounting at either 45° or 30°/60°.

Cable Entry: Provision for conduit entry in back and ends.

Design Life: 30+ years. [What is Design Life?](#)

■ Technical Information

TuscanAngledClassI	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
L650mm x H145mm x W114mm - 30/60 Degree angle				
D892-2-1500N-TB-CA	1419	15.5	92	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	5.3	CRI>80	45	L70B10>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	-	-
	Dimensions			
D892-2-2200N-TB-CA	2059	22.5	92	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	5.3	CRI>80	45	L70B10>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	-	-
	Dimensions			
D892-2-1500W-TB-CA	1348	15.5	87	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	5.3	CRI>80	45	L70B10>100,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	D	-	-
	Dimensions			
D892-2-2200W-TB-CA	1956	22.5	87	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	5.3	CRI>80	45	L70B10>100,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	D	-	-
	Dimensions			
L1250mm x H145mm x W114mm - 30/60 Degree angle				
D892-4-3200N-TB-CA	2990	33.7	89	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	8.8	CRI>80	45	L70B10>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	-	-
	Dimensions			

TuscanAngledClassII	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
L1250mm x H145mm x W114mm - 30/60Degree angle				
D892-4-4200N-TB-CA	3883	44.9	86	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	8.8	CRI>80	45	L70B10>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	-	-
	Dimensions			
L1250mm x H145mm x W114mm - 30/60Degree angle				
D892-4-3200W-TB-CA	2840	33.7	84	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	8.8	CRI>80	45	L70B10>100,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	D	-	-
	Dimensions			
L1250mm x H145mm x W114mm - 30/60Degree angle				
D892-4-4200W-TB-CA	3689	44.9	82	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	8.8	CRI>80	45	L70B10>100,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	D	-	-
	Dimensions			
L1550mm x H145mm x W114mm - 30/60Degree angle				
D892-5-3700N-TB-CA	3420	37.3	92	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	10.7	CRI>80	45	L70B10>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	-	-
	Dimensions			
L1550mm x H145mm x W114mm - 30/60Degree angle				
D892-5-5500N-TB-CA	4905	55.5	88	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	10.7	CRI>80	45	L70B10>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	-	-
	Dimensions			

TuscanAngledClassII	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
L1550mm x H145mm x W114mm - 30/60 Degree angle				
D892-5-3700W-TB-CA	3249	37.3	87	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	10.7	CRI>80	45	L70B10>100,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	D	-	-
	Dimensions			
L650mm x H121mm x W121mm - 45 Degree angle				
D893-2-1500N-TB-CA	1419	15.5	92	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	5.3	CRI>80	45	L70B10>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	-	-
	Dimensions			
D893-2-2200N-TB-CA	2059	22.5	92	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	5.3	CRI>80	45	L70B10>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	-	-
	Dimensions			
D893-2-1500W-TB-CA	1348	15.5	87	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	5.3	CRI>80	45	L70B10>100,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	D	-	-
	Dimensions			

TuscanAngledClassI	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
L650mm x H121mm x W121mm - 45 Degree angle				
D893-2-2200W-TB-CA	1956	22.5	87	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	5.3	CRI>80	45	L70B10>100,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	D	-	-
	Dimensions			
L1250mm x H121mm x W121mm - 45 Degree angle				
D893-4-3200N-TB-CA	2990	33.7	89	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	8.8	CRI>80	45	L70B10>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	-	-
	Dimensions			
D893-4-4200N-TB-CA	3883	44.9	86	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	8.8	CRI>80	45	L70B10>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	-	-
	Dimensions			
D893-4-3200W-TB-CA	2840	33.7	84	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	8.8	CRI>80	45	L70B10>100,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	D	-	-
	Dimensions			
D893-4-4200W-TB-CA	3689	44.9	82	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	8.8	CRI>80	45	L70B10>100,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	D	-	-
	Dimensions			

TuscanAngledClassII	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
L1550mm x H121mm x W121mm - 45 Degree angle				
D893-5-3700N-TB-CA	3420	37.3	92	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	10.7	CRI>80	45	L70B10>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	-	-
	Dimensions			
<hr/>				
D893-5-5500N-TB-CA	4905	55.5	88	4000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	10.7	CRI>80	45	L70B10>110,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	C	-	-
	Dimensions			
<hr/>				
D893-5-3700W-TB-CA	3249	37.3	87	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	10.7	CRI>80	45	L70B10>100,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	D	-	-
	Dimensions			
<hr/>				
D893-5-5500W-TB-CA	4660	55.5	84	3000
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	10.7	CRI>80	45	L70B10>100,000h
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	100,000	D	-	-
	Dimensions			

Fitting Options

Class II + In-rush Limiter	-CD
Class II + Surge Protection	-CC
Class II + Surge Protection + In-rush Limiter	-CB
Anti-Graffiti Diffuser Coating	-AG
Coastal Paint Finish (Zone 2)	-Z2
Class II Only	-CA
Emergency luminaire monitoring module (CEAG)	-EC
Textured Black	-TB
Textured White	-TW
DALI-2 Dimming / Monitoring	-DA

- For paint colour options, please replace -TB with required paint code.
- HT Applies for standard version. For any options, please contact technical sales on +44 (0)20 8254 2022 or email technical@designplan.co.uk.
- -EC not available on 650mm versions, 1550mm 5500lm version, or recessed versions.
- For Class II product with Surge Protection and In-rush Limiter, please replace -CA with -CB.
- For Class II product with Surge Protection, please replace -CA with -CC.
- For Class II product with In-rush Limiter, please replace -CA with -CD.

