



Obex Trunking

CMS/Trunking/Dummy Bodies

Class I

Surface

Obex Trunking is a cable management system specifically designed for custodial environments.

Standard Colours

Textured White

Product Information

Obex Trunking provides a cable management system for our ligature resistant [Obex](#) and [Obex Tuneable White](#) luminaires which are specifically designed for challenging environments, such as custodial facilities. Obex Trunking's applications include police stations and law courts. Each application is unique and will be catered to your requirements.

Housing: Zinc coated steel body

Paint: Polyester powder coat. [All Colour Options Available Here.](#)

Mounting: Cornice.

Luminaires: [Obex](#) and [Obex Tuneable White](#)

Technical Information

ObexTrunking	Output (Lum/Im)	Load (W)	Efficacy (lm/W)	CCT (K)
L200mm				
OBX-G1-DUM-200-TW	-	-	-	-
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	-	-	-	-
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/Im)	Nightlight Output (Lum/Im)
	-	-	-	-
	Dimensions			
	166mm x 166mm			
L350mm				
OBX-G1-DUM-350-TW	-	-	-	-
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	-	-	-	-
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/Im)	Nightlight Output (Lum/Im)
	-	-	-	-
	Dimensions			
	166mm x 166mm			

ObexTrunking	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
L450mm				
OBX-G1-DUM-450-TW	-	-	-	-
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	-	-	-	-
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	-	-	-	-
	Dimensions			
	166mm x 166mm			
L654mm				
OBX-G1-DUM-650-TW	-	-	-	-
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	-	-	-	-
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	-	-	-	-
	Dimensions			
	166mm x 166mm			
L850mm				
OBX-G1-DUM-850-TW	-	-	-	-
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	-	-	-	-
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	-	-	-	-
	Dimensions			
	166mm x 166mm			
L1000mm				
OBX-G1-DUM-1000-TW	-	-	-	-
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	-	-	-	-
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	-	-	-	-
	Dimensions			
	166mm x 166mm			
L1250mm				
OBX-G1-DUM-1250-TW	-	-	-	-
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	-	-	-	-
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	-	-	-	-
	Dimensions			
	166mm x 166mm			

ObexTrunking	Output (Lum/lm)	Load (W)	Efficacy (lm/W)	CCT (K)
L1548mm				
OBX-G1-DUM-1550-TW	-	-	-	-
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	-	-	-	-
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	-	-	-	-
	Dimensions			
	166mm x 166mm			
Extension unit 280mm-360mm				
OBX-G1-DUM-X300-TW	-	-	-	-
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	-	-	-	-
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	-	-	-	-
	Dimensions			
	166mm x 166mm			
Corner Unit with window for camera				
OBX-G1-90D-CAM-TW	-	-	-	-
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	-	-	-	-
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	-	-	-	-
	Dimensions			
	166mm x 166mm			
Corner unit with blank front panel				
OBX-G1-90D-DUM-TW	-	-	-	-
	Weight (kg)	CRI	High Temp (°C)	LED Lifetime
	-	-	-	-
	Driver lifetime (up to hours)	LED Energy Rating	Emergency Output (Lum/lm)	Nightlight Output (Lum/lm)
	-	-	-	-
	Dimensions			
	166mm x 166mm			

■ **Fitting Options**

Textured White

-TW
